

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)

[FR4X4YL6](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

A. System Overview

**PANDUIT**<sup>®</sup>

**PHYSICAL INFRASTRUCTURE SYSTEMS**

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

O. Labeling & Identification


P. Cable Management Accessories

Q. Index

**UL LISTED 4x4 FiberRunner<sup>®</sup> Routing System**

**Cable Fills for 4x4 FiberRunner<sup>®</sup> Cable Routing System**

The maximum amounts may vary according to the cable fill installation methods, straightness of cables, etc.



4x4 FiberRunner <sup>®</sup> Cable Routing System								
Fill/Pile Up	Internal Area (in <sup>2</sup> )	Diameter 1.6mm 0.063"	Diameter 2.0mm 0.079"	Diameter 3.0mm 0.118"	Fiber Optic Ribbon Interconnect Cable Diameter 5.20mm 0.205"	Category 6A (SD) Diameter 6.1mm 0.240"	Category 6A Diameter 7.6mm 0.300"	Category 6 Diameter 6.1mm 0.240"
<b>40% Fill</b>								
2" Pile Up	8.9	1142	731	325	108	79	50	79
3" Pile Up	13.58	1743	1116	496	165	120	77	120
4" Pile Up	17.6	2259	1446	643	213	156	100	156
<b>50% Fill</b>								
2" Pile Up	8.9	1428	914	406	135	98	63	98
3" Pile Up	13.58	2179	1394	620	206	150	96	150
4" Pile Up	17.6	2824	1807	803	267	195	124	195
<b>60% Fill</b>								
2" Pile Up	8.9	1714	1097	487	162	118	76	118
3" Pile Up	13.58	2615	1673	744	247	180	115	180
4" Pile Up	17.6	3389	2169	964	320	233	149	233


**Channel cutting instructions:** For optimum results, use a miter box and saw. For larger quantities use a plastic cutting saw blade for clean, burr-free cuts. Recommend: Carbide 80T and 100T; .090" thickness, .125" kerf.

The above cable diameters represent the nominal Panduit cable diameter per performance level. For specific cable fill information based on specific part numbers, please contact Panduit customer service.

**4x4 FiberRunner<sup>®</sup> Routing System – Channel and Covers**

- Robust 4x4 system ideal for use with smaller cable counts
- Multiple spillout options provide versatility to mate to various equipment and rack configurations
- QuikLock<sup>™</sup> Couplers and Brackets reduce system installation time dramatically
- Channel, covers, fittings and other non-metallic system components made from V-0 flame class rated material
- Compatible with all sizes of Panduit<sup>®</sup> FiberRunner<sup>®</sup> and Panduit<sup>®</sup> Fiber-Duct<sup>™</sup> Routing Systems, cable management, and racks
- Compliant with the applicable tests in Telcordia GR-63-CORE Network Equipment Building Systems (NEBS) Level 3

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>4x4 FiberRunner<sup>®</sup> Channel</b>			
<b>FR4X4YL6</b>	Used to carry the cables horizontally throughout the system. Accepts hinged cable retainers FRCR4BL-X, hinged cover FRHC4YL6, or split hinged cover FRSHC4YL6. Use QuikLock <sup>™</sup> Coupler FRBC4X4YL to attach channel and/or fittings.	6	36
<b>4x4 Snap-On Hinged Cover</b>			
<b>FRHC4YL6</b>	Optional snap-on hinged cover for channel FR4X4YL6. Hinge feature enables positioning of cover at angles between 30° to 90°.	6	36
<b>4x4 Split Hinged Cover</b>			
<b>FRSHC4YL6</b>	Optional split hinged cover for the channel FR4X4YL6. Creates radiused 3/4" (19mm) opening for easy access to add or remove cables. Snap-on hinge feature enables positioning of cover at angles between 30° and 90°.	6	36
<b>Cable Retainer for 4x4 System</b>			
<b>FRCR4BL-X</b>	Cable retainer holds cable in the channel when cover is not used. Install anywhere on channel, near the coupler or every 18" (457mm). Black color only.	10	100



For other colors replace YL (Yellow) with OR (Orange) or BL (Black).  
 Order number of feet required, in multiples of standard 6' length increments.  
 Order number of cable retainers required, in multiples of Standard Package Quantity.