

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1774911](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

HC-A 4-ESTS

Order No.: 1774911



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774911>

HEAVYCON male insert, A4 series, 4-pos., screw connection without wire protection

Commercial data	
EAN	4017918122249
Pack	10 pcs.
Customs tariff	85366990
Weight/Piece	0.01848 KG
Catalog page information	Page 423 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
01/31/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data	
Note	For housing HC-D7
Connection method	Screw connection
Tightening torque	0.25 Nm
Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
Pollution degree	3

HC-A 4-ESTS Order No.: 1774911

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774911>

Surge voltage category	III
Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Number of positions	4
Insertion/withdrawal cycles	≥ 500
Design	A4
Connection in acc. with standard	IEC / EN
Conductor cross section	0.5 mm ² ... 1.5 mm ²
Connection cross section AWG	20 ... 16
Stripping length of the individual wire	5 mm
Assembly instructions	Connectors may be operated only when there is no load/voltage.

Material data

Inflammability class acc. to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	230 V (Conductor-PE)
	400 V (Conductor-Conductor)
Rated surge voltage	4 kV
Rated current	10 A

Certificates / Approvals



Certification CSA, GOST, UL


CSA

Nominal voltage U _N	600 V
Nominal current I _N	10 A

HC-A 4-ESTS Order No.: 1774911
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774911>


Diagrams/Drawings

Diagram




Derating diagram: Series HC-A 3-E..S / HC-A 4-E..S

Dimensioned drawing



Male insert

Schematic diagram



Connector pin assignment connection side: Left pin; right socket

HC-A 4-ESTS Order No.: 1774911

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774911>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;