

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2294636](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Extract from the online catalog

FLK 40/EZ-DR/ 150/SLC

Order No.: 2294636

The illustration shows version FLK 40/EZ-DR/200/SLC



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294636>

Round cable sets, with 40-pos. socket strips in fixed lengths (50 cm steps) to connect to 32-channel I/O cards of the SLC 500, length 1.5 m

| Commercial data | |
|--------------------------|--------------------|
| EAN | 4017918149000 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Weight/Piece | 0.2249 KG |
| Catalog page information | Page 194 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
10/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

| General | |
|---|------------------|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |

FLK 40/EZ-DR/ 150/SLC Order No.: 2294636

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294636>

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Number of positions | 40 |
| Number of positions, control side | 40 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 40 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 1.5 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| Test voltage | 500 V AC (50 Hz, 1 min) |
| External diameter | 10 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |
| Standards/regulations | DIN EN 60352-4 |
| | IEC 352-4 |

Certificates / Approvals



Certification

GOST

FLK 40/EZ-DR/ 150/SLC Order No.: 2294636

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294636>

Address

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;