

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)  
[2812034](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



Extract from the online catalog

## UK 4-TG-P/P

Order No.: 2812034

The illustration shows version UK 4-TG



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>

Basic terminal block with screw connection, for component and fuse connectors, cross section: 0.2 - 4 mm<sup>2</sup>, AWG: 28 - 12, width: 6.2 mm, color: gray

| Commercial data          |                    |
|--------------------------|--------------------|
| EAN                      | 4017918107871      |
| Pack                     | 50 Pcs.            |
| Customs tariff           | 85369010           |
| Weight/Piece             | 0.010333 KG        |
| Catalog page information | Page 321 (CL-2007) |

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003



<http://www.download.phoenixcontact.com>  
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

| General               |      |
|-----------------------|------|
| Number of levels      | 1    |
| Number of connections | 2    |
| Color                 | gray |
| Insulating material   | PA   |

UK 4-TG-P/P Order No.: 2812034

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>

|                                    |    |
|------------------------------------|----|
| Inflammability class acc. to UL 94 | V2 |
|------------------------------------|----|

**Dimensions**

|                  |         |
|------------------|---------|
| Width            | 6.2 mm  |
| Length           | 42.5 mm |
| Height NS 35/7,5 | 47 mm   |
| Height NS 35/15  | 54.5 mm |
| Height NS 32     | 52 mm   |

**Technical data**

|                                  |   |
|----------------------------------|---|
| Maximum load current             | 16 A (with 4 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage              | 6 kV  |
| Pollution degree                 | 3   |
| Surge voltage category           | III   |
| Insulating material group        | I   |
| Connection in acc. with standard | IEC 60947-7-1   |
| Nominal current I <sub>N</sub>   | 16 A  |
| Nominal voltage U <sub>N</sub>   | 500 V   |

**Connection data**

|  |                      |
|--|----------------------|
| Conductor cross section solid min.   | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.   | 4 mm <sup>2</sup>    |
| Conductor cross section stranded min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section stranded max.                                      | 4 mm <sup>2</sup>    |
| Conductor cross section AWG/kcmil min.                                     | 24                   |
| Conductor cross section AWG/kcmil max                                      | 12                   |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 2.5 mm <sup>2</sup>  |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid min.                           | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                           | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                        | 0.2 mm <sup>2</sup>  |

UK 4-TG-P/P Order No.: 2812034

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>

|   |                      |
|---|----------------------|
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm <sup>2</sup>  |
| Cross-section with insertion bridge, solid max.   | 1.5 mm <sup>2</sup>  |
| Cross-section with insertion bridge, stranded max.                                      | 1.5 mm <sup>2</sup>  |
| Type of connection  | Screw connection     |
| Stripping length  | 9 mm                 |
| Internal cylindrical gage   | A3                   |
| Screw thread  | M3                   |
| Tightening torque, min  | 0.6 Nm               |
| Tightening torque max   | 0.8 Nm               |

### Certificates / Approvals

Approval logo



#### CUL

|                                |       |
|--------------------------------|-------|
| Nominal voltage U <sub>N</sub> | 600 V |
| Nominal current I <sub>N</sub> | 20 A  |
| AWG/kcmil                      | 28-12 |

#### UL

|                                |               |
|--------------------------------|---------------|
| Nominal voltage U <sub>N</sub> | 600 V         |
| Nominal current I <sub>N</sub> | 20 A          |
| AWG/kcmil                      | 28-12         |
| Certification                  | CUL, GOST, UL |

UK 4-TG-P/P Order No.: 2812034

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>
**Accessories**

| Item | Designation | Description |
|------|-------------|-------------|
|------|-------------|-------------|

**Assembly**

|         |                               |   |
|---------|-------------------------------|---|
| 3003224 | ATP-UK                        | Separating plate, for visual and electrical separation of terminal groups, width: 1.5 mm, color: Gray   |
| 3022218 | CLIPFIX 35                    | Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 mounting rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray |
| 3003020 | D-UK 4/10                     | Cover, width: 1.8 mm, color: gray   |
| 1201442 | E/UK                          | End clamp, for supporting the electronic base. If mounted vertically, 2 end clamps are required in each case  |
| 1201028 | NS 32 AL UNPERF 2000MM        | G rail 32 mm (NS 32)  |
| 1201280 | NS 32 CU/120QMM UNPERF 2000MM | G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m   |
| 1201358 | NS 32 CU/35QMM UNPERF 2000MM  | G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m   |
| 1201002 | NS 32 PERF 2000MM             | G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m  |
| 1201015 | NS 32 UNPERF 2000MM           | G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m  |
| 0801762 | NS 35/ 7,5 CU UNPERF 2000MM   | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m   |
| 0801733 | NS 35/ 7,5 PERF 2000MM        | DIN rail, material: Steel, perforated, height 7.5 mm, width 35 mm, length: 2 m  |
| 0801681 | NS 35/ 7,5 UNPERF 2000MM      | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m  |
| 1201756 | NS 35/15 AL UNPERF 2000MM     | DIN rail, deep-drawn, high profile, unperforated, 1.5 mm thick, material: Aluminum, height 15 mm, width 35 mm, length 2 m   |
| 1201895 | NS 35/15 CU UNPERF 2000MM     | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m  |
| 1201730 | NS 35/15 PERF 2000MM          | DIN rail, material: Steel, perforated, height 15 mm, width 35 mm, length: 2 m   |
| 1201714 | NS 35/15 UNPERF 2000MM        | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m   |
| 1201798 | NS 35/15-2,3 UNPERF 2000MM    | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m   |

**Bridges**

|         |          |   |
|---------|----------|---|
| 0201155 | EB 2- 6  | Insertion bridge, 2-pos., fully insulated             |
| 0201142 | EB 3- 6  | Insertion bridge, 3-pos., fully insulated             |
| 0201139 | EB 10- 6 | Insertion bridge, 10-pos., divisible, fully insulated |

UK 4-TG-P/P Order No.: 2812034

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>

**Marking**

|         |                  |   |
|---------|------------------|---|
| 1007222 | SBS 6:UNBEDRUCKT | Marker cards for modular terminal blocks, color: white  |
| 1050499 | ZB 6:SO/CMS      | Zack strip, 10-section, divisible, special printing, marking according to customer requirements |

**Tools**

|         |             |  |
|---------|-------------|--|
| 1205053 | SZS 0,6X3,5 | Screwdriver, bladed, matches all screw terminal blocks up to 4.0 mm <sup>2</sup> connection cross section, blade: 0.6 x 3.5 mm, without VDE approval |
|---------|-------------|--|

**Drawings**

Circuit diagram



UK 4-TG-P/P Order No.: 2812034  
<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2812034>

---

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2008 Phoenix Contact  
Technical modifications reserved;