

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2948827](#)

For any questions, you can email us directly:
sales@integrated-circuit.com



Extract from the online catalog

EMG 12-OV- 24DC/240AC/1

Order No.: 2948827

The illustration shows version EMG 12-OV, with AC voltage output, max. 1 A



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2948827>

Power optocoupler, with light indicator and protection circuits in the input and output circuits, input: 24 V DC, output: 24-280 V AC/max. 1 A

Commercial data	
EAN	4017918083496
Pack	10 pcs.
Customs tariff	85364190
Weight/Piece	0.0481 KG
Catalog page information	Page 129 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
06/07/2007



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data	
Nominal input voltage U_N	24 V DC
Input voltage range in reference to U_N	0.8 ... 1.2
Switching threshold "0" signal in reference to U_N	≤ 0.4
Switching threshold "1" signal in reference to U_N	≥ 0.8

EMG 12-OV- 24DC/240AC/1 Order No.: 2948827

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2948827>

Typical input current at U_N	6.8 mA
Typical response time	(max. one half cycle - zero-voltage crossing)
Typical turn-off time	(max. one half cycle - zero-current crossing)
Status display	Yellow LED
Name of protection	Polarity protection
	Surge protection
Protective circuit/component	Polarity protection diode
	Varistor
Transmission frequency	10 Hz

Output data

Output nominal voltage	240 V AC
Output nominal voltage range	24 V AC ... 280 V AC (50 Hz ... 60 Hz)
Limiting continuous current	1 A
Min. load current	50 mA
Leakage current	3.5 mA
Surge current	125 A (t = 10 ms)
Max. load value	78 A ² s (I ² x t where t = 10 ms)
Peak offstate voltage	600 V (Periodic peak reverse voltage)
Voltage drop at max. limiting continuous current	≤ 1.5 V
Output circuit	2-conductor floating
Name of protection	RC element
Protective circuit/component	RC element

Connection data

Type of connection	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

General data

Width	12.5 mm
-------	---------

EMG 12-OV- 24DC/240AC/1 Order No.: 2948827

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2948827>

Height	102 mm
Depth	75 mm
Test voltage input/output	3.5 kV AC
Ambient temperature (operation)	-20 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Assembly instructions	Mounted in rows with zero spacing: Horizontal/not in rows: Any
Operating mode	100% operating factor
Degree of protection	IP20
Inflammability class in acc. with UL 94 (housing)	V0
Standards/regulations	DIN VDE 0110
Rated surge voltage / insulation	Basic insulation

Certificates / Approvals



Certification

GOST

Accessories


Item	Designation	Description
------	-------------	-------------

Marking

2947035	EMG-GKS 12	Equipment marker, width 12 mm
---------	------------	-------------------------------

Diagrams/Drawings

Diagram




- ① In rows with zero spacing
- ② stand-alone device

EMG 12-OV- 24DC/240AC/1 Order No.: 2948827

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2948827>

Circuit diagram



EMG 12-OV- 24DC/240AC/1 Order No.: 2948827

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2948827>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;