

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[2959256](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

UM 72-PROFIL

CM



► General data

Profile housing, for mounting at a right-angle on NS 35/7.5 . The profile width is 72 mm.



**Zur Zeit ist kein
 Produktfoto vorhanden**

Order number	2959256	
Type	UM 72-PROFIL	CM
Barcode number	4017918086107	
Unit pack	1 Centimeter	
Customs tariff	39162010900	

► Technical data

General		
Housing material	PVC	
Color	green	
Dimensions / positions		
Width	72 mm	
Technical data		
Inflammability class acc. to UL 94	V0	



Documentation

Order key

	Profile width [mm]	Profile length [cm]	Color
UM	25 45 72 100 108 122	Please indicate length in [cm]	GN = green Special colors on request

Order example

Order key	Profile width [mm]	Profile length [cm]	Color
UM	25 45 72 100 108 122	Please indicate length in [cm]	GN = green Special colors on request

► Accessories

Item	Designation	Description
Assembly		
2959382	UM 72-FE	UM 72-FE foot element, 72 mm wide, for mounting on NS 32 or NS 35/7.5, below profile housing UM 72.
2959366	UM 72-LG 10	Profile housing and board base, 10 mm wide module, consisting of two side elements
2959337	UM 72-SE	UM 72-SE side element, 5 mm wide, PCB width: 72 mm
2959340	UM 72-SEFE/L	UM 72-SEFE/L side element with foot, 5 mm wide (left), for mounting on NS 32 or NS 35/7.5. PCB width: 72 mm
2959353	UM 72-SEFE/R	UM 72-SEFE/R side element with foot, 5 mm wide (right), for mounting on NS 32 or NS 35/7.5. PCB width: 72 mm
2906487	UM 72-SEPEF/L	UM 72- SEPEF/L side element with foot, 5 mm wide (left), for mounting on NS 32 or NS 35/7.5, with PE contact to the mounting rail. PCB width: 72 mm
2976077	UMK- BF	Mounting flange, for mounting directly on the wall

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved