

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Bel Fuse Inc.](#)
[PL40-1](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

RED INDICATES ORIGINAL

DASH NO	FIG	CABLES ACCOMMODATED	A DIM	B FLATS	C HEX	ASSEMBLE PER	REVISONS			1-0014		SH 1
							REV	ED	DESCRIPTION	DWN	APPROVED	DATE
C 4	C	DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND IS TO BE USED ONLY FOR THE PURPOSES AND IN ACCORDANCE WITH THE PROCEDURES AND INSTRUCTIONS SET FORTH IN THIS DOCUMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION.					AF	BB15	ADDED NOTE A/W/G/A & REDRAWN	3/6	1/12/92	3/26/92

DASH NO	FIG	CABLES ACCOMMODATED	A DIM	B FLATS	C HEX	ASSEMBLE PER
-1/A		RG-58				
-U1/A		ESSEX 621-715				
-2/A		RG-59				
-2A		BELDEN 8279				
-2B		AT&T 730A				
-U2	1.3	RG-223	.960	.437	.437	TAI-101
-3A		RG-55				
-4		RG-122				
-U4		BELDEN 821R				
-5/A		RG-174				
-U5/A		RG-187				
-5A		RG-196				
-5B		HEWLETT-PACKARD 8120-1107				
-U5B		BELDEN 9231	1.001	.500	.500	TAI-119
-6		RG-5				
-U6		RG-6				
-21		RG-303				
-U21		RG-180				
-22		GRUMMAN 6C756P1				
-31		RG-187 DBL SH.D				
-U31		BELDEN 8228	.960	.437	.437	TAI-101
-32		275-3981 MICRODOT				
-U32		516-589 AMPEX				
-37		810 RAYCHEM				
-U37		RG-304				
-41		924R BELDEN				
-44		BRAND-REX 8749				
-U44		GORE COBCC032				
-51		88281 BELDEN	1.001	.500	.500	TAI-119
-U51		89120 BELDEN				
-52		89556 BELDEN				
-U52	1.3	734A, AT&T	.960	.437	.437	TAI-101
-63		RG-405				
-U63		RG-402				TAI-130
-141	2					
-U141						

FIG 1
- 1 SHOWN

FIG 2
- 086 SHOWN

FIG 3
- 1 SHOWN

INCH	MM
.005	0.13
.030	0.76
.095	2.44
.125	3.18
.250	6.35
.312	7.92
.350	8.89
.437	11.10
.500	12.70
.624	15.85
.680	17.28
.848	21.64
1.001	25.43
1.848	46.98

IF SAFETY WIRE & BEND RELIEF SPRING REQUIRED ADD SUFFIX "SBR" TO MODEL NO. (NOT AVAILABLE WITH CABLE GROUPS -5, -U5, -6E, -U5E, -S1, -U51, -S2, -U52, -B3, -U63, -086, -U086, -141 & -U141)

IF BEND RELIEF SPRING REQUIRED ADD SUFFIX "BR" TO MODEL NO. (SEE FIG 3) (NOT AVAILABLE WITH CABLE GROUPS -6, -U6, -6E, -U6E, -S1, -U51, -S2, -U52, -B3 & -U63)

IF SAFETY WIRE REQUIRED ADD SUFFIX "S" TO MODEL NO (PL40S/UPL40S)

4. DASH NO DENOTES CABLE GROUP EXCEPT "U" PREFIX DENOTES 75 OHM VERSION

3. MALE TYPE TNC COAXIAL CABLE PLUG BOTH 50 & 75 OHM VERSIONS

2. FINISH: TFS-1A (NICKEL)

1. ALL DIM ARE IN INCHES

FOR CABLE GROUPS -1 & -U1 SUPPLY 1 EA ACA1 FOR CABLE GROUPS -2 & -U2 SUPPLY 1 EA ACA2 FOR CABLE GROUPS -5 & -U5 SUPPLY 1 EA ACAS MAY BE ASSEMBLED TO CABLE/CONNECTOR ASSY USING 3M SCOTCHGRIP NO. 1089 PLASTIC ADHESIVE, OR EQUIV.)

IF PLASTIC STRAIN RELIEF REQUIRED, ADD SUFFIX "BT" TO MODEL NO. (ONLY AVAILABLE WITH -1, -U1, -2, -U2, -5, -U5)

QTY	DESCRIPTION	PART NUMBER	ITEM
1	1-0261	105-1016	XX 2
1	1-0244	1-0027	XX 2 .005
1	1-0217	1-0026	XX 2
1	1-0214	105-0489	DWN J S 3/18/90
1	1-0206	105-0241	CHK UH 3/23/90
1	1-0205	205-0001	ENGR JZ 3/23/92
1	1-0203	1-0203	APPN JZ 3-23-92
1	1-0203	NEXT ASSY	

TROMPETER RF connectivity		PL40/6/BR/SBR/ UPL40/6/BR/SBR	REV
MATERIAL	CODE IDENT	DRAWING NO.	REV
	14949	1-0014	AF
SCALE 2/1	DATE 5/12/86	SHEET 1 OF 2	