

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated](#)

[RL203-T](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)




# RL201 - RL207

## 2.0A RECTIFIER

### Features

- Low Reverse Current
- Low Forward Voltage Drop
- High Current Capability
- Plastic Material - U/L Flammability
- Classification 94V-0

**DISCONTINUED,  
NOT RECOMMENDED FOR NEW DESIGNS,  
USE 2A01G - 2A07G**



### Mechanical Data

- Case: DO-15, Molded Plastic
- Leads: Solderable per MIL-STD-202, Method 208
- Polarity: Color Band Denotes Cathode
- Approx Weight: 0.4 grams
- Mounting Position: Any

DO-15		
Dim	Min	Max
A	25.4	—
B	5.8	7.6
C	0.71	0.86
D	2.6	3.6

All Dimensions in mm


### Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.





Single phase, half wave, 60Hz, resistive or inductive load.

Characteristic	Symbol	RL 201	RL 202	RL 203	RL 204	RL 205	RL 206	RL 207	Unit
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current 9.5mm Lead Length @ $T_A=50$ C	$I_{(AV)}$	2.0						A	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	70						A	
Maximum Instantaneous Forward Voltage at 2.0A DC	$V_F$	1.0						V	
Maximum DC Reverse Current @ $T_A = 25$ C at Rated DC Blocking Voltage @ $T_A = 125$ C	$I_R$	5.0 50						A	
Maximum Full Load Reverse Current Full Cycle Average 9.5 mm lead length @ $T_L = 75$ C	$I_R$	30						A	
Typical Junction Capacitance (Note 1)	$C_J$	40						pF	
Typical Thermal Resistance	$R_{JC}$	40						C/W	
Operating and Storage Temperature Range	$T_J, T_{STG}$	-65 to 150						C	

Notes: 1. Measured at 1.0MHz and applied reverse voltage of 4.0 volts.



**DISCONTINUED,  
NOT RECOMMENDED FOR NEW DESIGNS,  
USE 2A01G - 2A07G**



**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

**DISCONTINUED,  
NOT RECOMMENDED FOR NEW DESIGNS,  
USE 2A01G - 2A07G**