

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Luminus Devices Inc.](#)  
[SBT-90-W65S-F71-NA102](#)


For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



## SBT-90 Binning and Labeling

### SBT-90 LEDs



#### Table of Contents

Table of Products.....	2
Shipping and Labeling Nomenclature .....	3
Bin Kit Ordering Nomenclature .....	4
Flux Binning Structure .....	5
Chromaticity Binning Structure .....	5
SBT-90 Bin Kit Codes.....	7

#### Introduction:

This document describes the binning and labeling nomenclature for SBT-90 Big Chip LED™ product as well as the orderable bin kits for each part.

With each build of parts, there is a distribution of performance in both flux and wave length or chromaticity. In order to guarantee specific performance for customers, each device is measured and subsequently grouped into flux and wavelength or chromaticity bins. Each individual package or reel of parts contains only one combination of flux and wavelength or chromaticity bin. Furthermore, bins are combined into orderable bin kits comprising of a selection of flux and wavelength or chromaticity bins to ease the ordering process.



## SBT-90 Binning and Labeling

### Table of Products

Products	Ordering Part Number	Description
SBT-90-W65S	SBT-90-W65S-F71-XX123	White Big Chip LED™ SBT-90 surface mount device consisting of a 9 mm <sup>2</sup> LED on a ceramic substrate, tray pack
SBT-90-WDLS	SBT-90-WDLS-F71-XX123	
SBR-90-W65S	SBR-90-W65S-R71-XX123	SBR-90 evaluation module consisting of a SBT-90 surface mount device mounted on an aluminum star-board
SBR-90-WDLS	SBR-90-WDLS-R71-XX123	
SBT-90-R	SBT-90-R-F75-xx123	SBT-90 surface mount device consisting of a 9.0 mm <sup>2</sup> LED on ceramic substrate
SBR-90-R	SBR-90-R-R75-xx123	SBR-90 evaluation module consisting of a SBT-90 surface mount device mounted on an aluminum star board



## SBT-90 Binning and Labeling

### SBT-90 Shipping and Labeling Nomenclature

All SBT-90 products are packaged and labeled with their respective bin as outlined in the following pages. Each package or reel will only contain one bin. The part number designation is as follows:

**A B C** — **1 2 3** — **D 4 5 E** — **F 6 7** — **G H** — **I 8**

Product Family	Chip Area	Color	Package Configuration	Flux Bin	Chromaticity Bin
----------------	-----------	-------	-----------------------	----------	------------------

Product Family	A - Package type: "S" denotes surface mount B - Lens type: "B" denotes window (no lens) C - Chip quantity: "T" denotes single chip, and "R" denotes prototyping board				
Chip Area	1 2 3 - Total LED chip area (mm <sup>2</sup> ) x 10: "90" denotes 9mm <sup>2</sup>				
Color	D - Color: "W" denotes white 4 5 - Color temperature: "65" denotes 6500K E - Color rendering: "S" (standard) denotes a typical CRI of 70				
Package Config.	F 6 7 - Package configuration (for internal use)				
Flux Bin	G H - Flux bin				
Chromaticity Bin	I 8 - Chromaticity bin				

#### Example:

The part number SBT-90-W65S-F71-NA-G4 refers to a 6500K standard CRI white, SBT-90 emitter, with a minimum flux range from 1,590 to 1,710 lumens and a chromaticity value within the box defined by the four points (0.313, 0.338), (0.321, 0.348), (0.322, 0.336), (0.312, 0.328).



## SBT-90 Binning and Labeling

### SBT-90 Bin Kit Ordering Nomenclature

All SBT-90 White products are sold in sets of flux and chromaticity bins called bin kits. Each bin kit specifies a minimum flux bin and a specific selection of chromaticity bins. The ordering part number designation is as follows:

**A B C** — **1 2 3** — **D 4 5 E** — **F 6 7** — **G H 8 9 0**

Product Family	Chip Area	Color	Package Configuration	Bin Kit
----------------	-----------	-------	-----------------------	---------

Product Family	A - Package type: "S" denotes surface mount B - Lens type: "B" denotes window (no lens) C - Chip quantity: "T" denotes single chip, and "R" denotes prototyping board			
Chip Area	1 2 3 - Total LED chip area (mm <sup>2</sup> ) x 10: "90" denotes 9mm <sup>2</sup>			
Color	D - Color: "W" denotes white 4 5 - Color temperature: "65" denotes 6500K E - Color rendering: "S" (standard) denotes a typical CRI of 70			
Package Config.	F 6 7 - Package configuration (for internal use)			
Bin Kit	G H - Flux bin 8 9 0 - Chromaticity bin kit code			

#### Example:

The ordering part number SBT-90-W65S-F71-NA101 refers to a 6500K standard CRI white, SBT-90 emitter, with a minimum flux value of 1,590 lumens and falling in the F4, F3, G4, G3, EF, and DG chromaticity bins.



## SBT-90 Binning and Labeling

### SBT-90 Binning Structure

SBT-90 LEDs are tested for luminous flux and chromaticity at a drive current of 9.0 A (1.0 A/mm<sup>2</sup>) and placed into one of the following luminous flux (FF) and chromaticity (WW) bins:

#### Flux Bins

Color	Flux Bin (FF)	Minimum Flux (lm) @ 9.0A	Maximum Flux (lm) @ 9.0A
W65S 6500K, Standard CRI (typ. 70)	NA	1,590	1,710
	NB	1,710	1,830

Color	Luminous Flux Bin (FF)	Minimum Flux	Maximum Flux
Red	BK	600	770
	BM	770	970


Color	Wavelength Bin (FF)	Minimum Wavelength @ 13.5A	Maximum Wavelength @ 13.5A
Red	R3	615	619
	R4	619	623
	R5	623	627

\*Note: Luminus maintains a +/- 6% tolerance on flux measurements.

Luminus maintains a +/- 2% tolerance on CRI measurements.

#### Chromaticity Bins

Luminus' Standard Chromaticity Bins: 1931 CIE Curve





## SBT-90 Binning and Labeling

The following tables describe the four chromaticity points that bound each chromaticity bin. Chromaticity bins are grouped together based on the color temperature.

6500K Chromaticity Bins		
Bin Code (WW)	CIEx	CIey
DG	0.307	0.311
	0.322	0.326
	0.323	0.316
	0.309	0.302
F3*	0.305	0.321
	0.313	0.329
	0.315	0.319
	0.307	0.311
F4*	0.303	0.330
	0.312	0.339
	0.313	0.329
	0.305	0.321
G3*	0.313	0.329
	0.321	0.337
	0.322	0.326
	0.315	0.319
G4*	0.312	0.339
	0.321	0.348
	0.321	0.337
	0.313	0.329
EF	0.302	0.335
	0.320	0.354
	0.321	0.348
	0.303	0.330
DE	0.283	0.304
	0.303	0.330
	0.307	0.311
	0.289	0.293
DF	0.289	0.293
	0.307	0.311
	0.309	0.302
	0.293	0.285

5700K Chromaticity Bins		
Bin Code (WW)	CIEx	CIey
DJ	0.322	0.324
	0.337	0.337
	0.336	0.326
	0.323	0.314
H3*	0.321	0.335
	0.329	0.342
	0.329	0.331
	0.322	0.324
H4*	0.321	0.346
	0.329	0.354
	0.329	0.342
	0.321	0.335
J3*	0.329	0.342
	0.337	0.349
	0.337	0.337
	0.330	0.331
J4*	0.329	0.354
	0.338	0.362
	0.337	0.349
	0.329	0.342
EH	0.320	0.352
	0.338	0.368
	0.338	0.362
	0.321	0.346

\*Sub-bins within ANSI defined quadrangles per ANSI C78.377-2008



## SBT-90 Binning and Labeling

### SBT-90 and SBR-90 Bin Kit Order Codes

The following tables describe the bin kit ordering codes for the SBT-90 and SBR-90. The flux and chromaticity bins included in the bin kit. Each kit specifies a minimum flux and the listed chromaticity bins. A maximum flux is not specified. Within each kit, Luminus may ship any part meeting or exceeding the minimum flux specification. Shipments will always meet the listed chromaticity bins. For information on ordering bin kits not listed below, please contact Luminus or an official distributor.

#### SBT-90 and SBR-90 Bin Kit Order Codes

Color	Luminous Flux		Chromaticity Bins	Kit Number
	Bin Kit Flux Code	Min. Flux		
White W65S 6500K, Standard CRI (typ. 70)	NA	1,590	F4, F3, G4, G3, EF, DG, DE, DF	NA100
			F4, F3, G4, G3, EF, DG	NA101
			F4, F3, G4, G3	NA102
	NB	1,710	F4, F3, G4, G3, EF, DG, DE, DF	NB100
			F4, F3, G4, G3, EF, DG	NB101
			F4, F3, G4, G3	NB102
White WDL5 6500K & 5700K Standard CRI (typ. 70)	NA	1,590	F4, F3, G4, G3, EF, DG, DE, DF H4, H3, J4, J3, EH, DJ	NA150
	NB	1,710	F4, F3, G4, G3, EF, DG, DE, DF H4, H3, J4, J3, EH, DJ	NB150
Color	Luminous Flux		Wavelength Bins	Kit Number
	Bin Kit Flux Code	Min. Flux		
Red	HK	600	R3, R4, R5	HK100
			R4	HK101
	HM	770	R3, R4, R5	HM100
			R4	HM101

The products, their specifications and other information appearing in this document are subject to change by Luminus Devices without notice. Luminus Devices assumes no liability for errors that may appear in this document, and no liability otherwise arising from the application or use of the product or information contained herein. None of the information provided herein should be considered to be a representation of the fitness or suitability of the product for any particular application or as any other form of warranty. Luminus Devices' product warranties are limited to only such warranties as accompany a purchase contract or purchase order for such products. Nothing herein is to be construed as constituting an additional warranty. No information contained in this publication may be considered as a waiver by Luminus Devices of any intellectual property rights that Luminus Devices may have in such information. Big Chip LEDs™ is a registered trademark of Luminus Devices, Inc., all rights reserved.

This product is protected by U.S. Patents 6,831,302; 7,074,631; 7,083,993; 7,084,434; 7,098,589; 7,105,861; 7,138,666; 7,166,870; 7,166,871; 7,170,100; 7,196,354; 7,211,831; 7,262,550; 7,274,043; 7,301,271; 7,341,880; 7,344,903; 7,345,416; 7,348,603; 7,388,233; 7,391,059 Patents Pending in the U.S. and other countries.