

## **Excellent Integrated System Limited**

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Sanken](#)  
[2SD2015](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# Darlington 2SD2015



**Silicon NPN Triple Diffused Planar Transistor**

**Application :** Driver for Solenoid, Relay and Motor and General Purpose


**Absolute maximum ratings (Ta=25°C)**

Symbol	Ratings	Unit
V <sub>CB0</sub>	150	V
V <sub>CE0</sub>	120	V
V <sub>EB0</sub>	6	V
I <sub>C</sub>	4	A
I <sub>B</sub>	0.5	A
P <sub>C</sub>	25(T <sub>C</sub> =25°C)	W
T <sub>J</sub>	150	°C
T <sub>stg</sub>	-55 to +150	°C

**Electrical Characteristics (Ta=25°C)**

Symbol	Conditions	Ratings	Unit
I <sub>CB0</sub>	V <sub>CB</sub> =150V	10max	μA
I <sub>EB0</sub>	V <sub>EB</sub> =6V	10max	mA
V <sub>(BR)CEO</sub>	I <sub>C</sub> =10mA	120min	V
h <sub>FE</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =2A	2000min	
V <sub>CE(sat)</sub>	I <sub>C</sub> =2A, I <sub>B</sub> =2mA	1.5max	V
V <sub>BE(sat)</sub>	I <sub>C</sub> =2A, I <sub>B</sub> =2mA	2.0max	V
f <sub>T</sub>	V <sub>CE</sub> =12V, I <sub>E</sub> =-0.1A	40typ	MHz
C <sub>OB</sub>	V <sub>CB</sub> =10V, f=1MHz	40typ	pF


**External Dimensions FM20(TO220F)**




**Typical Switching Characteristics (Common Emitter)**

V <sub>CC</sub> (V)	R <sub>L</sub> (Ω)	I <sub>C</sub> (A)	V <sub>BB1</sub> (V)	V <sub>BB2</sub> (V)	I <sub>B1</sub> (mA)	I <sub>B2</sub> (mA)	t <sub>on</sub> (μs)	t <sub>stg</sub> (μs)	t <sub>f</sub> (μs)
40	20	2	10	-5	10	-10	0.6typ	5.0typ	2.0typ


**I<sub>C</sub>-V<sub>CE</sub> Characteristics (Typical)**




**V<sub>CE(sat)</sub>-I<sub>B</sub> Characteristics (Typical)**




**I<sub>C</sub>-V<sub>BE</sub> Temperature Characteristics (Typical)**




**h<sub>FE</sub>-I<sub>C</sub> Characteristics (Typical)**




**h<sub>FE</sub>-I<sub>C</sub> Temperature Characteristics (Typical)**




**θ<sub>j-a</sub>-t Characteristics**



**f<sub>T</sub>-I<sub>E</sub> Characteristics (Typical)**



**Safe Operating Area (Single Pulse)**



**P<sub>C</sub>-T<sub>a</sub> Derating**

