

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Citizen Finedevice](#)
[CSX750ABB133.330MTR](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



*Part
Numbering
System*

Quartz Clock Oscillators

Example Part Number:

CM309 FB C 25.333333M TR

Product Family
For example:
 CMX-309
 CSX-750F
 CSX-750P
 CSX-750A
 CSX-750V

Packaging method
TR Tape & Reel (Minimum size depends on product family - see catalog)
B Bulk (Bags for through-hole, tubes or tape for SMT)

Frequency
 Numerical value, maximum characters as follows:
 XX.XXXXXX followed by "M" for MHz.

Frequency Tolerance (at Operating Temp.)

	Frequency in MHz	
A	+/-25ppm (-20 to +70C)	(Consult Factory)
B	+/-50ppm (-20 to +70C)	(Standard)
C	+/-100ppm (-10 to +70C)	(Standard)
F	+/-100ppm (-40 to +85C)	(Consult Factory)
G	+/-200ppm (-40 to +85C)	(Consult Factory)

Frequency Range	Supply Voltage	Load Condition	Duty Cycle	
CMX-309 Series				
FL 1.000-30.000 MHz	5V 50pf CMOS	10TTL 40-60%	45-55%	(Fundamental) (Standard)
FS 1.000-30.000 MHz	5V 50pf CMOS	10TTL 40-60%	45-55%	(Fundamental)
HW 30.001-66.667 MHz	5V 50pf CMOS	10TTL 40-60%	45-55%	(Overone) (Standard)
HS 30.001-66.667 MHz	5V 50pf CMOS	10TTL 40-60%	45-55%	(Overone)
FB 1.000-30.000 MHz	3V 30pf CMOS	40-60%	40-60%	(Fundamental) (Standard)
FA 1.000-30.000 MHz	3V 30pf CMOS	45-55%	45-55%	(Fundamental)
HB 30.001-50.040 MHz	3V 30pf CMOS	40-60%	40-60%	(Overone) (Standard)
HA 30.001-50.040 MHz	3V 30pf CMOS	45-55%	45-55%	(Overone)
CSX-750 (F, P, A)				
CSX-750: Please check spec sheets for suffix				
CSX-750 (VCXO)				
CSX-750V: Please check spec sheets for suffix				

Home