Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Analog Devices Inc.
130656-HMC972LP5E

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E

ANALOG DEVICES

Hittite
MICROWAVE PRODUCTS
FROM ANALOG DEVICES

Analog Devices Welcomes Hittite Microwave Corporation

NO CONTENT ON THE ATTACHED DOCUMENT HAS CHANGED

OBSOLETE



www.analog.com

www.hittite.com

THIS PAGE INTENTIONALLY LEFT BLANK

OBSOLETE

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Hittite MICROWAVE CORPORATION v00.1210

RoHS EARTH FRIENDLY

HMC972LP5E

GaAs MMIC ANALOG VARIABLE GAIN AMPLIFIER, 0.5 - 6.0 GHz

OBSOLETE

Typical Applications

The HMC972LP5E is ideal for:

- Cellular/3G Infrastructure
- WiBro / WiMAX / 4G
- Microwave Radio & VSAT
- Test Equipment and Sensors
- IF & RF Applications

Features

Wide Gain Control Range: -35 to +15 dB

High Output IP3: +28 dBm

Positive Analog Control: 0 to +5V

Can be configured with 1 or 2 Attenuators

32 Lead 5x5 mm SMT Package: 25 mm^2

Functional Diagram



General Description

The HMC972LP5E is an analog controlled variable gain amplifier composed of two identical voltage variable attenuators in combination with an InGaP HBT gain block MMIC amplifier which operates from 0.5 to 6 GHz, and can be controlled to provide anywhere from 15 dB of gain to 35 dB of attenuation. The HMC972LP5E delivers noise figure of 7.5 dB in its maximum gain state, with output IP3 of up to +28 dBm. The HMC972LP5E is housed in a RoHS compliant 5x5 mm QFN leadless package, and requires no external matching components.

Electrical Specifications, T_A = +25° C, 50 Ohm System, Vdd = ATT1Vdd = ATT2Vdd = +5V [1]

Parameter	Frequency	Min.	Typ.	Max.	Units
Insertion Gain (Vctl = 0V)	0.5 - 2.7 GHz 2.7 - 4.0 GHz 4.0 - 6.0 GHz	10.5 6	13 9 0		dB dB
Gain Control Range	0.5 - 4.0 GHz 4.0 - 6.0 GHz		50 42		dB
Input Return Loss (Vctl = 0V)			12		dB
Output Return Loss (Vctl = 0V)			10		dB
Output Power for 1dB Compression (Vctl = 0V)	0.5 - 2.7 GHz 2.7 - 4.0 GHz 4.0 - 6.0 GHz		16 13 6		dBm dBm
Output Third Order Intercept Point (Two-Tone Output Power= 0 dBm Each Tone) (Vctl = 0V)	0.5 - 2.7 GHz 2.7 - 4.0 GHz 4.0 - 6.0 GHz		29 26 20		dBm dBm
Noise Figure (Vctl = 0V)			7.5		dB
Idd		75	85	102	mA
ATT1Idd			0.2	0.3	mA
ATT2Idd			0.2	0.3	mA

[1] Unless otherwise noted, test conditions: ATT1 + AMP + ATT2 in cascade.

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

RoHS EARTH FRIENDLY

GaAs MMIC ANALOG VARIABLE GAIN AMPLIFIER, 0.5 - 6.0 GHz

Gain vs. Frequency Over Vctl [1]



Gain Over Temperature (Vctl = 0V) [1]



Gain vs. Vctl Over Temperature @ 0.5 GHz [1]



Gain vs. Vctl Over Temperature @ 2 GHz [1]



Gain vs. Vctl Over Temperature @ 4 GHz [1]



Gain vs. Vctl Over Temperature @ 6 GHz [1]



[1] ATT1 + AMP + ATT2

OBSOLETE

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

RoHS EARTH FRIENDLY

GaAs MMIC ANALOG VARIABLE GAIN AMPLIFIER, 0.5 - 6.0 GHz

Input Return Loss Over Vctl [1]



Input Return Loss Over Temperature (Vctl = 0V) [1]



Output Return Loss Over Vctl [1]



Output Return Loss Over Temperature (Vctl = 0V) [1]



Output IP3 vs. Vctl [1]



Output IP3 vs. Temperature (Vctl = 0V) [1]



[1] ATT1 + AMP + ATT2

OBSOLETE

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Output IP2 vs. Vctl [1]



Output IP2 vs. Temperature (Vctl = 0V) [1]



Noise Figure Over Temperature (Vctl = 0V) [1]



Output P1dB Over Temperature (Vctl = 0V) [1]



OBSOLETE

[1] ATT1 + AMP + ATT2

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

OBSOLETE

Insertion Loss vs. Vctl [2]



Insertion Loss vs. Temperature [2]



Input Return Loss vs. Vctl [2]



Output Return Loss vs. Vctl [2]



Input IP3 vs. Vctl [2]



Input IP3 vs. Temperature (Vctl = 0V) [2]



[2] ATT1 Only

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

RoHS EARTH FRIENDLY

GaAs MMIC ANALOG VARIABLE GAIN AMPLIFIER, 0.5 - 6.0 GHz

Absolute Maximum Ratings

RF Input Power	+12 dBm
Supply Voltage	5.5 Vdc
Channel Temperature	150 °C
Continuous Pdiss (T = 85 °C) (derate 8.5 mW/°C above 85 °C) [1]	0.55 W
Thermal Resistance (Junction to Exposed Ground Paddle)	120 °C/W
Storage Temperature	-65 to +150 °C
Operating Temperature	-40 to +85 °C
ESD Sensitivity (HBM)	Class 1A

Bias Voltage

Vdd (V)	Idd (Typ.) (mA)
+5V	90

ELECTROSTATIC SENSITIVE DEVICE
OBSERVE HANDLING PRECAUTIONS

OBSOLETE

Outline Drawing



NOTES:
1. PACKAGE BODY MATERIAL: ALUMINA
2. LEAD AND GROUND PADDLE PLATING: 30-80 MICROINCHES GOLD OVER 50 MICROINCHES MINIMUM NICKEL.
3. DIMENSIONS ARE IN INCHES [MILLIMETERS].
4. LEAD SPACING TOLERANCE IS NON-CUMULATIVE
5. PACKAGE WARP SHALL NOT EXCEED 0.05mm DATUM -C-
6. ALL GROUND LEADS AND GROUND PADDLE MUST BE SOLDERED TO PCB RF GROUND.
7. CLASSIFIED AS MOISTURE SENSITIVITY LEVEL (MSL) 1.

Package Information

Part Number	Package Body Material	Lead Finish	MSL Rating	Package Marking [1]
HMC972LP5E	RoHS-compliant Low Stress Injection Molded Plastic	100% matte Sn	MSL1 [2]	H972 XXXX

[1] 4-Digit lot number XXXX
[2] Max peak reflow temperature of 260 °C

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Pin Descriptions

Pin Number	Function	Description	Interface Schematic
1 - 11, 14, 17 - 20, 22, 23, 25, 27, 29, 30	N/C	No connection required. The pins are not connected internally; however, all data shown herein was measured with these pins connected to RF/DC ground externally.	
12	ATT2OUT	This port is matched to 50 Ohms. Blocking capacitor required.	
13	Vctl	Attenuation control voltage for the attenuators. 0V for minimum attenuation, 5V for maximum attenuation.	
15	ATT2VDD	Power Supply for attenuator 2. External bypass capacitor is required. See application circuit.	
16	ATT2IN	This port is matched to 50 Ohms. Blocking capacitor required. Attenuator performance is similar to HMC973LP3E	
21	AMPOUT	This port is matched to 50 Ohms. External Choke inductor and DC blocking capacitor are required. See application circuit.	
24	GND	This pin and the exposed ground paddle must be connected to RF/DC ground.	
26	AMPIN	This port is matched to 50 Ohms. Blocking capacitor required. Amplifier performance is similar to HMC589ST89E.	
28	ATT1OUT	This port is matched to 50 Ohms. Blocking capacitor required.	
31	ATT1VDD	Power supply for attenuator 1. External bias capacitor is required. See application circuit.	
32	ATT1IN	This port is matched to 50 Ohms. Blocking capacitor required. Attenuator performance is similar to HMC973LP3E	

OBSOLETE

For price, delivery, and to place orders, please contact Hittite Microwave Corporation:
20 Alpha Road, Chelmsford, MA 01824 Phone: 978-250-3343 Fax: 978-250-3373
Order On-line at www.hittite.com

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Application Circuit



OBSOLETE

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Evaluation PCB



OBSOLETE

List of Materials for Evaluation PCB 130656 [1]

Item	Description
J1 - J5	DC Connector Header
J6 - J11	PCB Mount SMA RF Connector
C1, C8, C9	10 nF Capacitor, 0402 Pkg
C2, C3, C7	1000 pF Capacitor, 0402 Pkg.
C4, C6	1000 pF Capacitor, 0603 Pkg.
C5	100 pF Capacitor, 0603 Pkg.
C12	2.2 µF Capacitor, CASE A Pkg.
L1	24 nH Inductor 0603 Pkg.
R1, R2	0 Ohm Resistor, 0402 Pkg.
R3	1.8 Ohm Resistor, 1206 Pkg.
U1	HMC972LP5E Variable Gain Amplifier
PCB [2]	130653 Evaluation PCB

[1] Reference this number when ordering complete evaluation PCB

[2] Circuit Board Material: Rogers 4350

The circuit board used in the application should use RF circuit design techniques. Signal lines should have 50 Ohm impedance while the package ground leads and exposed paddle should be connected directly to the ground plane similar to that shown. A sufficient number of via holes should be used to connect the top and bottom ground planes. The evaluation circuit board shown is available from Hittite upon request.

Distributor of Analog Devices Inc.: Excellent Integrated System Limited
Datasheet of 130656-HMC972LP5E - EVAL BOARD HMC972LP5E
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Notes:

OBSOLETE