

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

<u>Desco</u> <u>13205</u>

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



	STATSHIELD [®] METAL-OUT SERIES		
Low Charging	Specifications:		
Clear Zipper Opening	Standard Document ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/ESD S11.4		Meets Requirements of: ESD Protective Packaging Level 3 Technical Requirements
	Electrical Properties Surface Resistance:	Typical Values	Test Procedures/Method
	Outer Surface Inner Surface Discharge Shielding Charge Generation Capacitance Probe (to dissipate 1 KV)	1 x 10 ⁴ to < 1 x 10 ⁸ ohms 1 x 10 ⁴ to < 1 x 10 ¹¹ ohms <20 nJ Teflon: -0.03 nC/sq. in. Quartz: +0.10 nC/sq. in. <30 volts	ANSI/ESD STM11.11 ANSI/ESD STM11.11 ANSI/ESD STM11.31, EIA 541 Modified Incline Plane ANSI/EIA-541/Appendix E, 1 kV Discharge
ATTENDOS STATSHELDO® Longth (inches) Attendo Contentione Bacterio Paramiterio	Physical Properties: Film Thickness Width (Inside Dimensions) Length (Inside Dimensions)	Nominal 0.003" (0.0762mm) ±10% Nominal -0" / + 0.125" Nominal ± 0.125"	MIL-STD-3010, 1003
Loub-les Rolfs complete Rolfs	Light Transmission Puncture Resistance Heat Seal Non-corrosive Silicone Marking Adhesion	40% (Tobias) >10 lbs >10 lbs/in. Pass Not detected Pass	ASTM D-1003 MIL-STD-3010, 2065 375°F, 1/2 sec 60 psi MIL-STD-3010, M3005 ASTM E168 IPC-TM-650 2.4.1
Weld Seal + Weld Side Weld Seals 3/8 in. (±0.10) Soft Fold Bottom	Chemical Properties Corrosion	No effect on aluminum, copper, silv stainless steel, low carbon steel	er, Sn-Pb coated foil,
High Performance Static Dissipative Abrasion Resistant Coating Aluminum Shieding Layer Low Charging Static Dissipative Proprietary Polyester Layer			
Low Charging Static Dissipative Proprietary Inner Polyethylene Layer	2015/12/17, or Conflict Mine	ed materials, REACH substances of v rals are intentionally added in manufa 011/65/EU and Regulation (EC) No. 1	cturing this product. Ref:
Mixed Unsortable Plastic Scrap Mixed unsortable plastic scrap shall contain assorted pl of multiple grades that are co-extruded, bonded or lami together which are unsortable into individual grade Desco's bags are recyclable	Statshield [®] and Stattree [®] are F See Bag Selection Chart Click	Registered Trademarks of Desco Industri HERE lures subject to change without notice	Made in the United States of America
Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at <u>TB-7057</u> . STATSHIELD® BAG, SHIELDING, METAL-OUT CONSTRUCTION, ZIPPER, 0.003" (0.0762mm)			
DESCO	DESCO WEST: 3651 WAL PHONE (909) 627-8178 DESCO EAST: ONE COLG PHONE (781) 821-8370	NUT AVE., CHINO, CA 91710 WEB SITE GATE WAY, CANTON, MA 02021-1407	DRAWING DATE: NUMBER 13205 2016

© 2016 DESCO INDUSTRIES INC. Employee Owned