Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Harting
09195606953

For any questions, you can email us directly:
sales@integrated-circuit.com

D-Sub

Standard Versions

Number of contacts

9–37



SMT stamped solder pins, angled with grounding dies

Identification	No. of contacts	Part number	
Performance levels ▶ Explanations see page 05.184 Other performance levels on request		Performance level 3	Performance level 2
Male connector metal shell with dimples	9	09 55 166 78 . . 741	09 55 166 68 . . 741
	15	09 55 266 78 . . 741	09 55 266 68 . . 741
	25	09 55 366 78 . . 741	09 55 366 68 . . 741
	37	09 55 466 78 . . 741	09 55 466 68 . . 741
Female connector metal shell	9	09 55 156 76 . . 741	09 55 156 66 . . 741
	15	09 55 256 76 . . 741	09 55 256 66 . . 741
	25	09 55 356 76 . . 741	09 55 356 66 . . 741
	37	09 55 456 76 . . 741	09 55 456 66 . . 741
Packaging: 140 pieces on a reel			
Please insert digit for flange thread or fitted female screw locks			
M3 ▶ 11			
4-40 UNC ▶ 12			
non-removable fitted screw locks M3 ▶ 21			
non-removable fitted screw locks 4-40 UNC ▶ 22			

Samples

Male connector metal shell with dimples	9	If performance level 3 is required please order as substitute performance level 2	09 55 166 68 . . 333
	15		09 55 266 68 . . 333
	25		09 55 366 68 . . 333
	37		09 55 466 68 . . 333
Female connector metal shell	9		09 55 156 66 . . 333
	15		09 55 256 66 . . 333
	25		09 55 356 66 . . 333
	37		09 55 456 66 . . 333
Packaging **9, 15 contacts: 5 samples** **25, 37 contacts: 3 samples**			
Please insert digit for flange thread or fitted female screw locks			
4-40 UNC ▶ 12			
non-removable fitted screw locks 4-40 UNC ▶ 22			

Connector dimensions see page 05.187 Mating conditions see page 05.184