



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[155-30902](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

155-30902



Article Number: 155-30902

Standoff Bundling Clip, Panel Thickness .02" - .03", .54" Height, PA66HIRHS, Black, 500/box



Download drawing



Download spec sheet

## Base Data

Local Order Number 155-30902

Type SOC4 M.FT6

Color Black (BK)

Features and Benefits

- Standoff design secures the bundle away from the mounting hole.
- Design provides low insertion force and high extraction force.

Product Description Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using bundle or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.

Short Description Standoff Bundling Clip, Panel Thickness .02" - .03", .54" Height, PA66HIRHS, Black, 500/box

## Product Dimensions

Length L (Imperial) 2.2 "

Length L (Metric) 55.0 mm

Length L2 (Imperial) 0.8 "

Length L2 (Metric) 20.0 mm

Fixation Method Fir Tree

Length of Fir Tree 13.7 mm

Height H (Imperial) 0.54 "

Panel Thickness Max. (Imperial) 0.2 "

Panel Thickness Max. (Metric) 5.1 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.7 mm

Mounting Hole Diameter D (Imperial) 0.25 - 0.28 "

Mounting Hole Diameter D (Metric) 6.5 - 7.0 mm

Mounting Hole Diameter D Min. (Imperial) 0.283 "

Mounting Hole Diameter D Max. 0.275 " (Imperial)

Mounting Hole Diameter D Max. 7.0 mm (Metric)

Mounting Hole Diameter D Min. (Metric) 6.5 mm

## Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces



**Weight (Metric)** 1.6 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes