

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP210M4](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

SNP210M4



Article Number: 190-00102

Snapper Hose Clamps, .353"/.398" Min/Max Diameter, POM, White, 1000/pkg



Download spec sheet

Base Data

Local Order Number SNP210M4

Type SNP2

Color White (WH)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, .353"/.398" Min/Max Diameter, POM, White, 1000/pkg

Product Dimensions

Length L (Imperial) 0.83 "

Length L (Metric) 21.0 mm

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.23 "

Width W2 (Metric) 5.84 mm

Bundle Diameter Min. (Imperial) 0.334 "

Bundle Diameter Min. (Metric) 8.7 mm

Bundle Diameter Max. (Imperial) 0.4 "

Bundle Diameter Max. (Metric) 10.0 mm

Diameter Min. (Imperial) 0.353 "

Diameter Min. (Metric) 8.97 mm

Diameter Max. (Imperial) 0.398 "

Diameter Max. (Metric) 10.11 mm

Wall Thickness WT (Imperial) 0.067 "

Wall Thickness WT (Metric) 1.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 8000



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP210M4 - SNAPPER HOSE CLAMP WHITE

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Material Polyacetal (POM)

Material Shortcut POM

Flammability UL94 HB

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes