

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T50ML9M4](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T50ML9M4



Article Number: 113-05403

Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 1,000/pkg



Download spec sheet

### Base Data

Local Order Number T50ML9M4

Type T50ML

Color Natural (NA)

**Features and Benefits**

- Mount design secures firmly with any #10 Screw.
- Screw mount style creates low insertion and high extraction force.

**Product Description** Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

**Short Description** Screw Mount Tie, 50lb, 15.4", Max Bundle Diameter 4.0", #10 Screw, PA66HS, Natural, 1,000/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 15.4 "

Length L (Metric) 390.0 mm

Fixation Method fixing hole

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.7 mm

Height H (Imperial) 0.23 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.12 "

Bundle Diameter Min. (Metric) 3.0 mm

Bundle Diameter Max. (Imperial) 4.0 "

Bundle Diameter Max. (Metric) 100.0 mm

Mounting Hole Diameter D (Imperial) 0.22 "

Mounting Hole Diameter D (Metric) 5.5 mm

Mounting Hole Diameter D Max. 5.5 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.5 mm

### Logistics and Packaging



**Package Quantity (Metric)** 1000

**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes