

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03016](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-03016



Article Number: 170-03016

Fray Resistant Expandable Braided Sleeveing, 1.5" Dia., PET, Black, 50.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03016

Type BSPSC1120

Color Black (BK)

- Features and Benefits**
- Cuts with scissors without fraying ends enables field installations without need for hot knife.
 - Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.
 - Expands to 150% of easy installation and reduced assembly time requirements.

Product Description A versatile and economical general purpose braided sleeveing that resists fraying when cut with ordinary scissors.

Short Description Fray Resistant Expandable Braided Sleeveing, 1.5" Dia., PET, Black, 50.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Min. (Imperial) 1.25 "

Bundle Diameter Min. (Metric) 31.8 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 50.8 mm

Nominal Diameter (Imperial) 1-1/2 "

Nominal Diameter (Metric) 38.1 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 50.0 ft

Weight (imperial) 0.925 lbs

Weight (Metric) 0.42 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Operating Temperature -94°F to +257°F (-70°C to +125°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03016 - FRAY RESIS SLEEVING 1.5"DIA BLAC

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

UL Recognized (US and Canada) Yes