

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TELS-1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TELS-1



Article Number: 111-30000

Extended Length Tie, POM, Black, 10-50ft reels of strap and 300 heads/pkg



Download spec sheet

Base Data

Local Order Number TELS-1

Type EL-TY (TELS1)

Color Black (BK)

- Features and Benefits**
- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
 - Smooth strap prevents cable damage.
 - UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Product Description HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

Short Description Extended Length Tie, POM, Black, 10-50ft reels of strap and 300 heads/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1112.0 N

Length L (Imperial) 50.0 ft

Length L (Metric) 15200 mm

Fixation Method None

Releasable Closure No

Tie Closure steel pawl

Variant Extended Length

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Width W2 (Imperial) 0.8 "

Width W2 (Metric) 20.3 mm

Thickness T (Imperial) 0.06 "

Thickness T (Metric) 1.50 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 1

Carton Quantity 25

Weight (Metric) 0.6 kg

Material and Specifications

Material	Polyacetal (POM)
Material Shortcut	POM
Material Cable Tie	Polyacetal (POM)
Flammability	UL94 HB
Material Head	Polyacetal (POM)
Material Spacer	Polypropylene, UV-resistant (PPW)
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes