

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[SNP110C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## SNP110C2



Article Number: 190-00022

Snapper Hose Clamps, .237"/.264" Min/Max Diameter, POM, White, 100/pkg



Download spec sheet

### Base Data

Local Order Number SNP110C2

Type SNP1

Color White (WH)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Short Description** Snapper Hose Clamps, .237"/.264" Min/Max Diameter, POM, White, 100/pkg

### Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.148 "

Width W2 (Metric) 3.76 mm

Bundle Diameter Min. (Imperial) 0.3 "

Bundle Diameter Min. (Metric) 6.0 mm

Bundle Diameter Max. (Imperial) 0.26 "

Bundle Diameter Max. (Metric) 6.5 mm

Diameter Min. (Imperial) 0.237 "

Diameter Min. (Metric) 6.02 mm

Diameter Max. (Imperial) 0.264 "

Diameter Max. (Metric) 6.71 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6 mm

Wall Thickness WT (Imperial) 0.04 "

Wall Thickness WT (Metric) 1.0 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 25000



**Distributor of HellemanTyton: Excellent Integrated System Limited**

Datasheet of SNP110C2 - SNAPPER HOSE CLAMP WHITE

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Material** Polyacetal (POM)

**Material Shortcut** POM

**Flammability** UL94 HB

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes