

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T150M9X2](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T150M9X2



Article Number: 111-15619

Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number T150M9X2

Type T150M

Color Natural (NA)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 175.0 lbs

Minimum Tensile Strength (Metric) 780.0 N

Length L (Imperial) 21.0 "

Length L (Metric) 530.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.35 "

Width W (Metric) 8.9 mm

Bundle Diameter Min. (Imperial) 0.32 "

Bundle Diameter Min. (Metric) 8.0 mm

Bundle Diameter Max. (Imperial) 5.9 "

Bundle Diameter Max. (Metric) 150.0 mm

Thickness T (Imperial) 0.075 "

Cable Tie Head Length (Imperial) 0.55 "

Cable Tie Head Width (Imperial) 0.55 "

Thickness T (Metric) 1.9 mm

### Logistics and Packaging

Quantity Per bag

**Carton Quantity** 1000

**Weight (Metric)** 8.4 kg

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL-ZODZ2.E64139

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes