

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T150L9X2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T150L9X2



**Article Number:** 111-15419

**Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg**



Download spec sheet

### Base Data

**Local Order Number** T150L9X2

**Type** T150L

**Color** Natural (NA)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 175.0 lbs

**Minimum Tensile Strength (Metric)** 780.0 N

**Length L (Imperial)** 32.3 "

**Length L (Metric)** 820.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.35 "

**Width W (Metric)** 8.8 mm

**Bundle Diameter Min. (Imperial)** 0.32 "

**Bundle Diameter Min. (Metric)** 8.0 mm

**Bundle Diameter Max. (Imperial)** 9.6 "

**Bundle Diameter Max. (Metric)** 245.0 mm

**Thickness T (Imperial)** 0.079 "

**Thickness T (Metric)** 2 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 25 Pieces

**Carton Quantity** 500

## Material and Specifications

---

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Material</b>                      | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>             | PA66                             |
| <b>Flammability</b>                  | UL94 V2                          |
| <b>Halogenfree</b>                   | Yes                              |
| <b>Operating Temperature</b>         | -40°F to +185°F (-40°C to +85°C) |
| <b>ROHS Compliant</b>                | Yes                              |
| <b>Certification/Specification</b>   | MIL 53421<br>UL-ZODZ2.E64139     |
| <b>UL Listed (US and Canada)</b>     | No                               |
| <b>UL Recognized (US and Canada)</b> | Yes                              |