

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T150L0X2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T150L0X2



**Article Number:** 111-15405

**Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg**



Download spec sheet

### Base Data

**Local Order Number** T150L0X2

**Type** T150L

**Color** Black (BK)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Head design provides high tensile strength with very low insertion force.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 175.0 lbs

**Minimum Tensile Strength (Metric)** 780.0 N

**Length L (Imperial)** 32.3 "

**Length L (Metric)** 820.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.35 "

**Width W (Metric)** 8.8 mm

**Bundle Diameter Min. (Imperial)** 0.32 "

**Bundle Diameter Min. (Metric)** 8.0 mm

**Bundle Diameter Max. (Imperial)** 9.6 "

**Bundle Diameter Max. (Metric)** 245.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 25 Pieces

**Carton Quantity** 500

### Material and Specifications



**Material Shortcut** PA66

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** MIL 53421  
UL-ZODZ2.E64139

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes