

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T120MR9K2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T120MR9K2



Article Number: 113-12029

Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T120MR9K2

Type T120MR

Color Natural (NA)

Features and Benefits

- Part design applies easily to any #1/4" Screw
- Stud style provides low insertion and high extraction force.

Product Description Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

Short Description Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 535 N

Length L (Imperial) 15.6 "

Length L (Metric) 395.0 mm

Fixation Method fixing hole

Identification Plate Position none

Mounting Screw Type M6

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.6 mm

Height H (Imperial) 0.31 "

Height H (Metric) 7.9 mm

Bundle Diameter Min. (Imperial) 0.2 "

Bundle Diameter Min. (Metric) 5.0 mm

Bundle Diameter Max. (Imperial) 4.0 "

Bundle Diameter Max. (Metric) 102.0 mm

Mounting Hole Diameter D (Imperial) 0.26 "

Mounting Hole Diameter D (Metric) 6.5 mm

Thickness T (Imperial) 0.07 "

Cable Tie Head Length (Imperial) 1.12 "

Cable Tie Head Width (Imperial) 0.51 "

(Metric) Mounting Hole Diameter D Min. (Metric) 6.5 mm

Thickness T (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50 Pieces

Weight (Metric) 5.8 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes