

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[CTT20R9C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## CTT20R9C2



Article Number: 112-51919

Compression Tie, 4" Long, 20lb Tensile Strength, PA66, Natural, 100/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number CTT20R9C2

Type CTT20R

Color Natural (NA)

**Features and Benefits**

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Product Description** The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Compression Tie, 4" Long, 20lb Tensile Strength, PA66, Natural, 100/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 20.0 lbs

Minimum Tensile Strength (Metric) 90.0 N

Length L (Imperial) 4.0 "

Length L (Metric) 101.6 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.1 "

Width W (Metric) 2.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 0.51 "

Bundle Diameter Max. (Metric) 13.0 mm

Thickness T (Imperial) 0.043 "

Thickness T (Metric) 1.1 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

**Weight (Metric)** 0.228 kg

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL62275

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes