

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TM1SF10C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TM1SF10C2



**Article Number:** 151-40119

**Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** TM1SF10C2

**Type** TM1SF

**Color** White (WH)

**Features and Benefits**

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution.
- The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Product Description** HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

**Short Description** Push Mount, .25" Hole Dia., .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg

### Product Dimensions

**Length L (Imperial)** 0.62 "

**Length L (Metric)** 15.8 mm

**Fixation Method** with Arrowhead / Push Mount (Mounts)

**Width W (Imperial)** 0.4 "

**Width W (Metric)** 10.2 mm

**Cable Tie Width Max. (Imperial)** 0.2 "

**Cable Tie Width Max. (Metric)** 5.0 mm

**Height H (Imperial)** 0.18 "

**Height H (Metric)** 4.6 mm

**Height H2 (Imperial)** 0.18 "

**Height H2 (Metric)** 4.6 mm

**Panel Thickness Max. (Imperial)** 0.13 "

**Panel Thickness Max. (Metric)** 3.40 mm

**Panel Thickness Min. (Imperial)** 0.13 "

**Panel Thickness Min. (Metric)** 3.30 mm

**Mounting Hole Diameter D (Imperial)** 0.25 "

**Mounting Hole Diameter D (Metric)** 6.35 mm

**Mounting Hole Diameter D Max. (Imperial)** 0.28 "

**Mounting Hole Diameter D Max. (Metric)** 6.35 mm

**Mounting Hole Diameter D Min. (Metric)** 6.35 mm

### Logistics and Packaging

<b>Package Quantity (Metric)</b>	100 Pieces
<b>Carton Quantity</b>	15000 Pieces
<b>Weight (Metric)</b>	1 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes