

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T50LDH9C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T50LDH9C2



Article Number: 117-05402

Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T50LDH9C2

Type T50LDH

Color Natural (NA)

- Features and Benefits**
- The tie contains a dual locking design to secure two bundles at once.
 - Head design can also provide spacing between parallel bundles.
 - Bent tail allows for quick insertion into head.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 15.6 "

Length L (Metric) 395.0 mm

Bundle Diameter 2nd Loop Max. (Imperial) 2.0 "

Fixation MethodNone

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 50.0 mm

Bundle Diameter 1st Loop Max. (Imperial) 4.0 "

Bundle Diameter 1st Loop Max. (Metric) 101.6 mm

Thickness T (Imperial) 0.055 "

Cable Tie Head Length (Imperial) 0.53 "

Cable Tie Head Width (Imperial) 0.22 "

Bundle Diameter 2nd Loop Max. 50.8 mm
(Metric)

Thickness T (Metric) 1.4 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes