

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[MB4A10C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## MB4A10C2



**Article Number: 151-28421**

**Adhesive Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 100/pkg**



Download spec sheet

### Base Data

**Local Order Number** MB4A10C2

**Type** MB4A

**Color** White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Adhesive Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 100/pkg

### Product Dimensions

**Length L (Imperial)** 1.12 "

**Length L (Metric)** 28.5 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.12 "

**Width W (Metric)** 28.5 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.6 mm

**Height H (Imperial)** 0.22 "

**Height H (Metric)** 5.6 mm

**Mounting Hole Diameter D (Imperial)** 0.18 "

**Mounting Hole Diameter D (Metric)** 4.6 mm

**Mounting Hole Centers (Imperial)** 0.8 "

**Mounting Hole Diameter D Max.** 4.6 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 4.6 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)



**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes