

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T18MR9M4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T18MR9M4



Article Number: 113-00028

Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw, PA66, Natural, 100/pkg



Download spec sheet

Base Data

Local Order Number T18MR9M4

Type T18MR

Color Natural (NA)

Features and Benefits • Mount design secures firmly on any #4 Screw
 • Screw mount style creates low insertion and high extraction force.

Product Description Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

Short Description Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 18.0 lbs

Minimum Tensile Strength (Metric) 80 N

Length L (Imperial) 4.3 "

Length L (Metric) 110.0 mm

Fixation Method fixing hole

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.1 "

Width W (Metric) 2.5 mm

Height H (Imperial) 0.17 "

Height H (Metric) 4.2 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 0.8 "

Bundle Diameter Max. (Metric) 20.0 mm

Mounting Hole Diameter D (Imperial) 0.12 "

Mounting Hole Diameter D (Metric) 3.1 mm

Thickness T (Imperial) 0.039 "

Mounting Hole Diameter D Max. 3.1 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 3.1 mm

Thickness T (Metric) 1.0 mm



Logistics and Packaging

| | |
|---------------------------|-------|
| Quantity Per | bag |
| Package Quantity (Metric) | 1000 |
| Carton Quantity | 10000 |

Material and Specifications

| | |
|-------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |
| Certification/Specification | UL |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | Yes |