

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T30RSF0M4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T30RSF0M4



Article Number: 126-00702

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RSF0M4

Type T30RSF(U)

Color Black (BK)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
 - Push mount style creates low insertion and high extraction force.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 6.3 "

Length L (Metric) 161.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 31.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.4 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 0.9 mm

Mounting Hole Diameter D (Imperial) 0.19 - 0.22 "

Mounting Hole Diameter D (Metric) 4.7 - 5.5 mm

Mounting Hole Diameter D Min. (Imperial)	0.19 "	Mounting Hole Diameter D Max. (Imperial)	0.22 "	Thickness T (Imperial)	0.05 "
Mounting Hole Diameter D Max. (Metric)	5.6 mm	Mounting Hole Diameter D Min. (Metric)	4.8 mm		
Thickness T (Metric)	1.2 mm				

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	1000
Carton Quantity	5000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes