

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[HellermannTyton](#)  
[132-00010](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

132-00010



Article Number: 132-00010

Button Head Tie, 105lb, 9.6" Long, Max Bundle Diameter 2.6", PA66HSUV, Black, 50/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 132-00010

Type BT105R

Color Black (BK)

**Features and Benefits**

- Unique two piece tie allows parallel entry and exit through the head for easy assembly.
- PA66HIRHS material make it ideal for trucking and heavy equipment applications.

**Product Description** The button head tie is a two piece tie providing for parallel entry and exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise prior to insertion into the head, enabling bi-directional looping.

**Short Description** Button Head Tie, 105lb, 9.6" Long, Max Bundle Diameter 2.6", PA66HSUV, Black, 50/pkg

## Product Dimensions

Minimum Tensile Strength (Imperial) 105.0 lbs

Minimum Tensile Strength (Metric) 467 N

Length L (Imperial) 9.6 "

Length L (Metric) 244.4 mm

Fixation Method Connector Clip

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.2 "

Width W (Metric) 5.6 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 2.6 "

Bundle Diameter Max. (Metric) 66.7 mm

## Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50

Carton Quantity 1000

## Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 132-00010 - BUTTON HEAD TIE 105LB 9.6"L BLK

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Flammability** UL94 HB

**Material Head** Polyamide 6.6 heat stabilized (PA66HS)

**Operating Temperature** -65°F to +212°F (-54°C to +100°C)