



Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[156-00068](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

156-00068



Article Number: 156-00068

Heavy Duty Fir Tree with Cable Tie, 9" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00068

Type WSSFT9A

Color Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
 - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
 - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

Product Description HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

Short Description Heavy Duty Fir Tree with Cable Tie, 9" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 9.0 "

Length L (Metric) 228.0 mm

Fixation Method Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Width W2 (Imperial) 0.51 "

Width W2 (Metric) 13.0 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.1 mm

Height H2 (Imperial) 0.36 "

Height H2 (Metric) 9.0 mm

Bundle Diameter Max. (Imperial) 2.3 "

Bundle Diameter Max. (Metric) 57.0 mm

Disc Diameter (Imperial) 0.9 "

Disc Diameter (Metric) 21.6 mm

Panel Thickness Max. (Imperial) 0.26 "

Panel Thickness Max. (Metric) 6.5 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 1.0 mm

Mounting Hole Diameter D (Metric) 8.75 - 9.25 mm

Mounting Hole Diameter D Min. (Imperial) 0.34 "

Mounting Hole Diameter D Max.0.36 "
(Imperial)

Mounting Hole Diameter D Max.9.25 mm
(Metric) 8.75 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 500 Pieces

Weight (Metric) 6.4 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -65°F to +212°F (-54°C to +100°C)

ROHS Compliant Yes