

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[IXYS Corporation](#)

[MKE11R600DCGFC](#)

For any questions, you can email us directly:



sales@integrated-circuit.com

MKE 11R600DCGFC

CoolMOS™ 1) Power MOSFET with SiC Diode Boost topology

$I_{D25} = 15\text{ A}$
 $V_{DSS} = 600\text{ V}$
 $R_{DS(on)\text{ max}} = 0.165\ \Omega$

Electrically isolated back surface
2500 V electrical isolation



MOSFET T			
Symbol	Conditions	Maximum Ratings	
V_{DSS}	$T_{VJ} = 25^\circ\text{C}$	600	V
V_{GS}		± 20	V
I_{D25}	$T_C = 25^\circ\text{C}$	15	A
I_{D90}	$T_C = 90^\circ\text{C}$	11	A
E_{AS}	single pulse } $I_D = 7.9\text{ A}; T_C = 25^\circ\text{C}$ repetitive }	522	mJ
E_{AR}		0.79	mJ
dV/dt	MOSFET dV/dt ruggedness $V_{DS} = 0 \dots 480\text{ V}$	50	V/ns

Features

- Silicon chip on Direct-Copper-Bond substrate
 - high power dissipation
 - isolated mounting surface
 - 2500 V electrical isolation
 - low drain to tab capacitance (< 40 pF)
- Fast CoolMOS™ 1) power MOSFET 4th generation
 - high blocking capability
 - lowest resistance
 - avalanche rated for unclamped inductive switching (UIS)
 - low thermal resistance due to reduced chip thickness
- Enhanced total power density
- SiC Boost Diode
 - no reverse recovery current

Symbol	Conditions	Characteristic Values			
		$(T_{VJ} = 25^\circ\text{C}, \text{ unless otherwise specified})$			
		min.	typ.	max.	
$R_{DS(on)}$	$V_{GS} = 10\text{ V}; I_D = 12\text{ A}$		150	165	m Ω
$V_{GS(th)}$	$V_{DS} = V_{GS}; I_D = 0.79\text{ mA}$	2.5	3	3.5	V
I_{DSS}	$V_{DS} = 600\text{ V}; V_{GS} = 0\text{ V}$			1	μA
				10	μA
I_{GSS}	$V_{GS} = \pm 20\text{ V}; V_{DS} = 0\text{ V}$			100	nA
C_{iss}	} $V_{GS} = 0\text{ V}; V_{DS} = 100\text{ V}$ $f = 1\text{ MHz}$		2000		pF
C_{oss}				100	
Q_g	} $V_{GS} = 0\text{ to }10\text{ V}; V_{DS} = 400\text{ V}; I_D = 12\text{ A}$		40	52	nC
Q_{gs}			9		nC
Q_{gd}			13		nC
$t_{d(on)}$	} Inductive switching $T_{VJ} = 125^\circ\text{C}$ $V_{GS} = 0/10\text{ V}; V_{DS} = 380\text{ V}$ $I_D = 12\text{ A}; R_G = 10\ \Omega$		12		ns
t_r			6		ns
$t_{d(off)}$			75		ns
t_f			4		ns
E_{on}			0.09		mJ
E_{off}			0.01		mJ
$E_{rec off}$	no reverse recovery current due to absence of minority carrier injection				mJ
R_{thJC}	with heat transfer paste (IXYS test setup)			1.1	K/W
R_{thJH}		1.35			K/W

Applications

- Switched mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)
- Power factor correction (PFC)

Advantages

- Easy assembly: no screws or isolation foils required
- Space savings
- High power density
- High reliability

¹⁾ CoolMOS™ is a trademark of Infineon Technologies AG.

MOSFET T Source-Drain Diode

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
($T_{VJ} = 25^{\circ}\text{C}$, unless otherwise specified)				
I_S	$V_{GS} = 0\text{ V}$		12	A
V_{SD}	$I_F = 12\text{ A}; V_{GS} = 0\text{ V}$	0.9	1.2	V
t_{rr}	$I_F = 12\text{ A}; -di_F/dt = 100\text{ A}/\mu\text{s}; V_R = 400\text{ V}$		390	ns
Q_{RM}			7.5	μC
I_{RM}			38	A

SiC Boost Diode D

Symbol	Conditions	Maximum Ratings	
V_{RRM}	$T_{VJ} = 25^{\circ}\text{C}$ to 150°C	600	V
I_{F25}	$T_C = 25^{\circ}\text{C}$	15	A
I_{F90}	$T_C = 90^{\circ}\text{C}$	9.5	A

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
V_F	$I_F = 8\text{ A}$ $T_{VJ} = 25^{\circ}\text{C}$		1.5	1.7
	$I_F = 8\text{ A}$ $T_{VJ} = 150^{\circ}\text{C}$			1.9
I_R	$V_R = V_{RRM}$	$T_{VJ} = 25^{\circ}\text{C}$	1	100
		$T_{VJ} = 150^{\circ}\text{C}$	10	μA
I_{FSM}	$t = 10\text{ ms}$ (50 Hz), sine; $T_{VJ} = 25^{\circ}\text{C}$			59
Q_C	$I_F = I_{Fmax}; V_R = 400\text{ V}; T_{VJ} = 150^{\circ}\text{C}$		19	nC
t_C	$di/dt = 200\text{ A}/\mu\text{s}^1$			10
R_{thJC}	} with heat transfer paste (IXYS test setup)		4.0	3.1
R_{thJH}				K/W

¹⁾ t_C is the time constant for the capacitive displacement current waveform (independent from T_{VJ} , I_{LOAD} and di/dt), different from t_r which is dependent on T_{VJ} , I_{LOAD} and di/dt .
 No reverse recovery time constant t_{rr} due to absence of minority carrier injection


Component

Symbol	Conditions	Maximum Ratings	
T_{VJ}	operating	-55...+150	$^{\circ}\text{C}$
T_{stg}	storage	-55...+125	$^{\circ}\text{C}$
V_{ISOL}	$I_{ISOL} < 1\text{ mA}; 50/60\text{ Hz}$	2500	V~
F_C	mounting force with clip	20...120	N

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
C_P	coupling capacity between shorted pins and mounting tab in the case		40	pF
d_S, d_A	pin - pin	1.7		mm
d_S, d_A	pin - backside metal	5.5		mm
Weight			9	g

IXYS **MKE 11R600DCGFC**

ISOPLUS i4™ Outline



DIM.	MILLIMETER		INCHES	
	MIN	MAX	MIN	MAX
A	4.83	5.21	0.190	0.205
A1	2.59	3.00	0.102	0.118
A2	1.17	2.16	0.046	0.085
b	1.14	1.40	0.045	0.055
b2	1.47	1.73	0.058	0.068
b4	2.54	2.79	0.100	0.110
C	0.51	0.74	0.020	0.029
D	20.80	21.34	0.819	0.840
D1	14.99	15.75	0.590	0.620
D2	1.65	2.03	0.065	0.080
E	19.56	20.29	0.770	0.799
E1	16.76	17.53	0.660	0.690
e	3.81 BSC		0.15 BSC	
L	19.81	21.34	0.780	0.840
L1	2.11	2.59	0.083	0.102
Q	5.33	6.20	0.210	0.244
R	2.54	4.57	0.100	0.180
W	0.10		0.004	

Die konvexe Form des Substrates ist typ. < 0.05 mm über der Kunststoffoberfläche der Bauteilunterseite
 The convex bow of substrate is typ. < 0.05 mm over plastic surface level of device bottom side




Fig. 1 Power dissipation




Fig. 2 Typ. output characteristics




Fig. 3 Typ. output characteristics



MKE 11R600DCGFC




Fig. 4 Typ. drain-source on-state resistance




Fig. 5 Drain-source on-state resistance




Fig. 6 Typ. transfer characteristics




Fig. 7 Forward characteristic of reverse diode




Fig. 8 Typ. gate charge




Fig. 9 Typ. capacitances




Fig. 10 Avalanche energy




Fig. 11 Drain-source breakdown voltage




Fig. 12 Forward characteristic of boost diode




Fig. 13 Drain current I_D versus case temperature T_C




Fig. 14 Typ. turn-on energy and switching times versus drain current, inductive switching




Fig. 15 Typ. turn-off energy and switching times versus drain current, inductive switching




Fig. 16 Typ. turn-on energy and switching times versus gate resistor, inductive switching




Fig. 17 Typ. turn-off energy and switching times versus gate resistor, inductive switching




Fig. 18 Typ. transient thermal impedances of IGBT with heat transfer paste (IXYS test setup)




Fig. 19 Typ. transient thermal impedances of boost diode with heat transfer paste (IXYS test setup)




Fig. 20 Definition of switching times