

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)
[17112202001](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

SEK · D-Sub · DIN 41612



Cables for insulation displacement termination

Identification	No. of contacts	Part number	Drawing	Dimensions in mm			
Flat cable grey UL AWM-style 2651 CSA	6	09 18 006 700	<p>Conductor material _____ Copper tinned Gauge _____ AWG 28/7 0.089 mm² Voltage rating _____ 300 V_{r.m.s.} Current rating at 25 °C _____ 2.1 A max. Capacity unbalanced _____ 45.9 pF/m Impedance unbalanced _____ 105 Ω Propagation delay _____ 4.9 ns/m nominal Insulation material _____ PVC Temperature rating (operating) _____ -20 °C ... +105 °C Temperature rating (static) _____ -30 °C ... +105 °C Flammability rating _____ UL: VW-1 Insulation resistance _____ > 100 MΩ/km</p>				
	9	09 18 009 700					
	10	09 18 010 700					
	14	09 18 014 700					
	15	09 18 015 700					
	16	09 18 016 700					
	18	09 18 018 700					
	20	09 18 020 700					
	24	09 18 024 700					
	25	09 18 025 700					
	26	09 18 026 700					
	28	09 18 028 700					
	30	09 18 030 700					
	34	09 18 034 700					
	37	09 18 037 700					
	40	09 18 040 700					
	50	09 18 050 700					
	60	09 18 060 700					
	64	09 18 064 700					
	Length per reel						
	30.48 m (100 feet)	1					
	100 m (328 feet)	4					
	Flat cable grey non-halogenated UL style 21447 for VW-1	6			09 18 006 700	<p>Conductor material _____ Copper tinned Gauge _____ AWG 28/7 0.089 mm² Voltage rating _____ 300 V_{r.m.s.} Current rating _____ 1.3 A Capacity unbalanced _____ 42.6 pF/m at 1 MHz Impedance unbalanced _____ 100 Ω Inductance _____ 0.56 μH/m Propagation delay _____ 4.8 ns/m Insulation material _____ Non-halogenated flame retardant Polyolefin Temperature rating _____ -40 °C ... +80 °C Insulation resistance _____ 10000 MΩ/km</p>	
		9			09 18 009 700		
		10			09 18 010 700		
		14			09 18 014 700		
		15			09 18 015 700		
16		09 18 016 700					
18		09 18 018 700					
20		09 18 020 700					
24		09 18 024 700					
25		09 18 025 700					
26		09 18 026 700					
28		09 18 028 700					
34		09 18 034 700					
37		09 18 037 700					
40		09 18 040 700					
50		09 18 050 700					
60		09 18 060 700					
64		09 18 064 700					
Length per reel							
30.48 m (100 feet)		1					

SEK