

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[A-TB381-TT02](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																																																	
A						<b>Material</b> Item a Clamp: Brass(CuZn),Ni plated Item b Terminal screw: Steel Zinc plating "-" slot type Item c Female contact:PhBz,Tin plated Item d Terminal (housing): Thermoplastic (UL94V-0) , GREEN			A																																																															
B						<b>Electrical</b> Voltage rating: 300VAC Current rating: 10A Wire range: Solid wire(AWG): 16-28 Stranded wire(AWG): 16-28 Torque(Lb-in): 1.7 Screw: M2 Wire strip length: 5-6mm Withstanding Voltage: 1.6KV Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval:			B																																																															
C									C																																																															
D									D																																																															
E									E																																																															
F	<table border="1"> <thead> <tr> <th colspan="2">DIMENSION</th> <th colspan="2">Tolerance</th> </tr> <tr> <th>L</th> <th>P</th> <th>DIM L</th> <th>DIM P</th> </tr> </thead> <tbody> <tr> <td>Nx3.81</td> <td>(N-1)x3.81</td> <td>±0.15</td> <td>±0.15</td> </tr> <tr> <td></td> <td></td> <td>±0.20</td> <td>±0.20</td> </tr> <tr> <td></td> <td></td> <td>±0.30</td> <td>±0.30</td> </tr> <tr> <td></td> <td></td> <td>±0.40</td> <td>±0.40</td> </tr> </tbody> </table> <p>N=Number of poles</p>					DIMENSION		Tolerance		L	P	DIM L	DIM P	Nx3.81	(N-1)x3.81	±0.15	±0.15			±0.20	±0.20			±0.30	±0.30			±0.40	±0.40	F																																										
DIMENSION		Tolerance																																																																						
L	P	DIM L	DIM P																																																																					
Nx3.81	(N-1)x3.81	±0.15	±0.15																																																																					
		±0.20	±0.20																																																																					
		±0.30	±0.30																																																																					
		±0.40	±0.40																																																																					
G	<p><b>RoHS compliant</b></p> <table border="1"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>19.04.2010</td> <td>Hellwig</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td><b>A-TB381-TTxx</b></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>ASS 4117 CO</td> <td>rev00</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td></td> <td>Replace</td> <td>Sheet</td> </tr> </table>					Scale	1:1				Date	Name	Customer-No.	TOLERANCE					Drawn	19.04.2010	Alex	X.	±0.50				Approved	19.04.2010	Hellwig	X.X	±0.30						ASSMANN WSW-No.	X.XX	±0.10						<b>A-TB381-TTxx</b>	DIM	TOL						Drawing-No.	X.°	±1°						ASS 4117 CO	rev00	Angle	TOL	Id.	Modification	Date	Name		Replace	Sheet	G
Scale						1:1				Date	Name	Customer-No.																																																												
TOLERANCE										Drawn	19.04.2010	Alex																																																												
X.	±0.50				Approved	19.04.2010	Hellwig																																																																	
X.X	±0.30						ASSMANN WSW-No.																																																																	
X.XX	±0.10						<b>A-TB381-TTxx</b>																																																																	
DIM	TOL						Drawing-No.																																																																	
X.°	±1°						ASS 4117 CO	rev00																																																																
Angle	TOL	Id.	Modification	Date	Name		Replace	Sheet																																																																
H						H																																																																		
	1	2	3	4	5	6	7																																																																	