

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[A-TB500-T202SB](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																																																										
A						Material ① Clamp: Brass, Ni plated ② Terminal screw: Steel Zinc plating "-" slot type ③ Wire guard solder pin: Brass, Tin plated ④ Terminal housing: Thermoplastic (UL94V-0), GREEN			A																																																																								
B						Electrical UL Voltage rating: 300VAC Current rating: 10A Wire range: Solid wire(AWG): 12-24 Stranded wire(AWG): 12-24 Torque(Lb-In): 3.5 Screw: M2.5 Wire strip length: 6-7mm Withstanding Voltage: 1.6KV Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval:			B																																																																								
C						DIMENSION <table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td>L</td> <td>Nx5.0</td> </tr> <tr> <td>P</td> <td>(N-1)x5.0</td> </tr> </table> N=Number of poles			L	Nx5.0	P	(N-1)x5.0	C																																																																				
L						Nx5.0																																																																											
P	(N-1)x5.0																																																																																
D	<table border="1" style="display: inline-table; border-collapse: collapse;"> <thead> <tr> <th>Poles</th> <th>Tolerance</th> </tr> <tr> <th colspan="2">DIM L&DIM P</th> </tr> </thead> <tbody> <tr> <td>4p-8p</td> <td>±0.15</td> </tr> <tr> <td>9p-14p</td> <td>±0.25</td> </tr> <tr> <td>15p-20p</td> <td>±0.35</td> </tr> <tr> <td>21p-24p</td> <td>±0.40</td> </tr> </tbody> </table>			Poles	Tolerance	DIM L&DIM P		4p-8p	±0.15	9p-14p	±0.25	15p-20p	±0.35	21p-24p	±0.40	D																																																																	
Poles	Tolerance																																																																																
DIM L&DIM P																																																																																	
4p-8p	±0.15																																																																																
9p-14p	±0.25																																																																																
15p-20p	±0.35																																																																																
21p-24p	±0.40																																																																																
E	<p>RECOMMENDER PCB LAYOUT</p>								E																																																																								
F	<p>RoHS compliant</p>								F																																																																								
G						<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>19.04.2010</td> <td>Hellwig</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="2" rowspan="2"> </td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>			Scale	1:1				Date	Name	Customer-No.	TOLERANCE					Drawn	19.04.2010	Alex	X.	±0.50				Approved	19.04.2010	Hellwig	X.X	±0.30							X.XX	±0.10							DIM	TOL							X.°	±1°							Angle	TOL	Id.	Modification	Date	Name									ASSMANN WSW-No. A-TB500-T2xxSB		G
Scale						1:1				Date	Name	Customer-No.																																																																					
TOLERANCE					Drawn	19.04.2010	Alex																																																																										
X.	±0.50				Approved	19.04.2010	Hellwig																																																																										
X.X	±0.30																																																																																
X.XX	±0.10																																																																																
DIM	TOL																																																																																
X.°	±1°																																																																																
Angle	TOL	Id.	Modification	Date	Name																																																																												
H							Drawing-No. ASS 4101 CO rev00		H																																																																								
	1	2	3	4	5	6	7																																																																										