

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09456000105](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HARTING PROFINET Type B Cable Outdoor, 4-wire, Cat. 5, PVC



PROFINET Type B Cable Outdoor, 4-wire, Cat. 5, PVC



Advantages

- Suitable for PROFINET cabling Category 5 / Class D according to ISO/IEC 11801 respectively EN 50173-1 and ISO/IEC 24702 respectively EN 50173-3
- Capable flexible cords
- Applicable for industrial premises
- RoHS conform, UL listed, flame retardant

General

This data cable is suitable for PROFINET cabling according to type B in industrial premises and areas. It is useable for flexible cords especially for outdoor applications. The core is fitted with 4 wires twisted to quad that allows the transmission of Fast Ethernet 10/100Mbit/s. It is designed for fast assembling with the easy-stripping tool and can be assembled with all HARTING 4-pole RJ45 connectors.

Description

PROFINET Type B Cable Outdoor
4-wire, Cat. 5, PVC

20 m ring
50 m ring
100 m ring
500 m reel

Order number

09 45 600 0135
09 45 600 0145
09 45 600 0105
09 45 600 0115



- Wire: Stranded tinned copper AWG 22/7
- Insulation: : PE Ø 1.56 mm (+/-0.003)
- Inner sheath: Polyvinylchloride (PVC)
- Overall screen: Aluminate foil overlapped, tinned copper wire braid, braid coverage about 85%
- Outer sheath: Polyvinylchloride (PVC), flame retardant

Color code: wh, ye, bu, or
Color of inner sheath: white
Color of outer sheath: black, RAL 9005
Overall diameter: 6.3 mm – 6.7 mm

HARTING PROFINET Type B Cable Outdoor, 4-wire, Cat. 5, PVC



Technical Characteristics

Performance Category 5 according to EN 50288-2-1:2003, IEC 61156-5:2002

Mechanical Characteristics

Minimal bending radius During installation: 5 x diameter
After installation: 3 x diameter
Torsion strength +/-180°on 1m, 10,000cycles

Electrical Characteristics at 20°C

Surface transfer impedance at 10 MHz 20 mOhm/m
Loop resistance max. 120 Ohm/km
Insulation resistance min. 500 MOhm x km
Signal runtime 5.3 ns/m
Characteristic impedance at 100 MHz 100 Ohm +/- 5 Ohm
Test voltage (wire/wire/screen rms 50Hz 1min) 2000V

Chemical Characteristics

Flame retardant UL 1685 (CSA FT 4)
Free of hazardous substances RoHS 2002/95/EG
Sunlight resistant UL 1581 Sec.1200

Thermal Characteristics

Permissible temperature range - 40° C to + 70° C
During laying - 20° C to + 60° C

Printing

HARTING INDUSTRIAL ETHERNET STRANDED CABLE CAT 5 PLUS * UV protected * 22AWG (SHIELDED) (UL) E119100 CMG or PLTC or AWM 2570 80°C 600V FT4 SUN RES * 94560001020300 "sequential length in metres" * "year/internal order number" "HARTING-LOGO"

Weight about

68 kg/km

HARTING PROFINET Type B Cable Outdoor, 4-wire, Cat. 5, PVC



Technical Characteristics

Frequency MHz	Attenuation dB/100m		NEXT dB	
	typ.	Cat 5 max*	typ.	Cat 5 min*
1	2.1	2.1	80	80
4	4	4	76	76
10	6.3	6.3	70	70
16	8	8	65	65
20	9	9	63	63
31.25	11.4	11.4	60	60
62.5	16.5	16.5	55	55
100	21.3	21.3	50	50

* EN 50288-2-1:2003