



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09641227210 - D-Sub Connector Plug, Male Pins 9 Position Through Hole Solder

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09641227210](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	5	4	3	2	1																																															
D					<p style="text-align: center;">SPECIFICATION</p> <p>Performance level PL2 Filter type C Capacitance 47pf±20% Working Voltage 100V Current rating 7.5 A Insulation Resistance >1GΩ</p> <p style="text-align: center;">Minimum Insertion Loss</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FREQUENCY (MHz)</th> <th>ATTENUATION dB</th> </tr> </thead> <tbody> <tr><td>5</td><td>-</td></tr> <tr><td>10</td><td>-</td></tr> <tr><td>50</td><td>-</td></tr> <tr><td>100</td><td>-</td></tr> <tr><td>500</td><td>30dB</td></tr> <tr><td>1000</td><td>35dB</td></tr> </tbody> </table>	FREQUENCY (MHz)	ATTENUATION dB	5	-	10	-	50	-	100	-	500	30dB	1000	35dB																																	
FREQUENCY (MHz)	ATTENUATION dB																																																			
5	-																																																			
10	-																																																			
50	-																																																			
100	-																																																			
500	30dB																																																			
1000	35dB																																																			
C																																																				
B	<p>PCB Layout, Component side</p>																																																			
A	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 15%;"></td> <td style="width: 15%;"></td> <td style="width: 15%;"></td> <td style="width: 15%; text-align: center;">Dat.</td> <td style="width: 15%; text-align: center;">Name</td> <td rowspan="2" style="text-align: center;"> <p>All Dim. in mm Orig. Size DIN A 4</p> </td> <td rowspan="2" style="vertical-align: top;"> D-Sub, male, straight, 9 Poles, with turned solder pin, fixing hole </td> <td style="text-align: right;">Mo/MS tab/ Scale</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Detail.</td> <td style="text-align: center;">CV</td> <td style="text-align: right;">1.5:1</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Insp.</td> <td style="text-align: center;">JB</td> <td rowspan="3" style="text-align: center;"> </td> <td rowspan="3" style="text-align: center; vertical-align: middle;"> TB 09641227210 </td> <td style="text-align: right;">Blatt/ Page</td> </tr> <tr> <td style="text-align: center;">36283</td> <td style="text-align: center;">09/12/11</td> <td style="text-align: center;">SD</td> <td style="text-align: center;">Stand.</td> <td></td> <td style="text-align: right;">1</td> </tr> <tr> <td style="text-align: center;">32802</td> <td style="text-align: center;">11/07/05</td> <td style="text-align: center;">JMDR</td> <td></td> <td></td> <td style="text-align: right;">1</td> </tr> <tr> <td style="text-align: center;">31058</td> <td style="text-align: center;">8-JUL-02</td> <td style="text-align: center;">CV</td> <td></td> <td></td> <td style="text-align: right;">1</td> </tr> <tr> <td style="text-align: center;">Mod.</td> <td style="text-align: center;">Dat.</td> <td style="text-align: center;">Name</td> <td colspan="3" style="text-align: center;"> HARTING EURL F-95972 Paris </td> <td style="text-align: center;">Sub.</td> <td></td> </tr> </table>							Dat.	Name	<p>All Dim. in mm Orig. Size DIN A 4</p>	D-Sub, male, straight, 9 Poles, with turned solder pin, fixing hole	Mo/MS tab/ Scale				Detail.	CV	1.5:1				Insp.	JB		TB 09641227210	Blatt/ Page	36283	09/12/11	SD	Stand.		1	32802	11/07/05	JMDR			1	31058	8-JUL-02	CV			1	Mod.	Dat.	Name	HARTING EURL F-95972 Paris			Sub.	
			Dat.	Name	<p>All Dim. in mm Orig. Size DIN A 4</p>	D-Sub, male, straight, 9 Poles, with turned solder pin, fixing hole	Mo/MS tab/ Scale																																													
			Detail.	CV			1.5:1																																													
			Insp.	JB		TB 09641227210	Blatt/ Page																																													
36283	09/12/11	SD	Stand.				1																																													
32802	11/07/05	JMDR					1																																													
31058	8-JUL-02	CV			1																																															
Mod.	Dat.	Name	HARTING EURL F-95972 Paris			Sub.																																														