



Distributor of Harting: Excellent Integrated System Limited

Datasheet of 09642227210 - D-Sub Connector Plug, Male Pins 15 Position Through Hole Solder

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)

[09642227210](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

5	4	3	2	1																																																									
D																																																													
C	<p style="text-align: right;">SPECIFICATION</p> <table style="width:100%;"> <tr> <td>Performance level</td> <td>PL2</td> </tr> <tr> <td>Filter type</td> <td>C</td> </tr> <tr> <td>Capacitance</td> <td>47pf±20%</td> </tr> <tr> <td>Working Voltage</td> <td>100v</td> </tr> <tr> <td>Current Rating</td> <td>7,5A</td> </tr> <tr> <td>Insulation Resistance</td> <td>>1GΩ</td> </tr> </table> <table border="1" style="width:100%; margin-top: 10px;"> <thead> <tr> <th>FREQUENCY (MHz)</th> <th>ATTENUATION dB</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>-</td> </tr> <tr> <td>10</td> <td>-</td> </tr> <tr> <td>50</td> <td>-</td> </tr> <tr> <td>100</td> <td>-</td> </tr> <tr> <td>500</td> <td>30dB</td> </tr> <tr> <td>1000</td> <td>35dB</td> </tr> </tbody> </table>				Performance level	PL2	Filter type	C	Capacitance	47pf±20%	Working Voltage	100v	Current Rating	7,5A	Insulation Resistance	>1GΩ	FREQUENCY (MHz)	ATTENUATION dB	5	-	10	-	50	-	100	-	500	30dB	1000	35dB																															
Performance level	PL2																																																												
Filter type	C																																																												
Capacitance	47pf±20%																																																												
Working Voltage	100v																																																												
Current Rating	7,5A																																																												
Insulation Resistance	>1GΩ																																																												
FREQUENCY (MHz)	ATTENUATION dB																																																												
5	-																																																												
10	-																																																												
50	-																																																												
100	-																																																												
500	30dB																																																												
1000	35dB																																																												
B	<p style="text-align: center;">PCB Layout, Component side</p>																																																												
A	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Dat.</td> <td style="text-align: center;">Name</td> <td rowspan="2" style="text-align: center;"> <small>All Dim. in mm Orig. Size DIN A 4</small> </td> <td rowspan="2" style="text-align: center;"> D-Sub, male, straight, 15 Poles, solder pins, dimples and fixing holes </td> <td rowspan="2" style="text-align: center;"> <small>M/MS tab/ Scale</small> 1.5:1 </td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Detail.</td> <td style="text-align: center;">CV</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Insp.</td> <td style="text-align: center;">JB</td> <td rowspan="3" style="text-align: center;"> HARTING EURL F-95972 Paris </td> <td rowspan="3" style="text-align: center;"> TB 09642227210 </td> <td rowspan="3" style="text-align: center;"> <small>Blatt/ Page</small> 1 / 1 </td> </tr> <tr> <td style="text-align: center;">36283</td> <td style="text-align: center;">09/12/11</td> <td style="text-align: center;">SD</td> <td style="text-align: center;">Stand.</td> <td></td> </tr> <tr> <td style="text-align: center;">33267</td> <td style="text-align: center;">17/11/05</td> <td style="text-align: center;">JMDR</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">31058</td> <td style="text-align: center;">8-JUL-02</td> <td style="text-align: center;">CV</td> <td></td> <td></td> <td></td> <td style="text-align: center;">Sub.</td> <td></td> </tr> <tr> <td style="text-align: center;">Mod.</td> <td style="text-align: center;">Dat.</td> <td style="text-align: center;">Name</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>																	Dat.	Name	 <small>All Dim. in mm Orig. Size DIN A 4</small>	D-Sub, male, straight, 15 Poles, solder pins, dimples and fixing holes	<small>M/MS tab/ Scale</small> 1.5:1				Detail.	CV				Insp.	JB	HARTING EURL F-95972 Paris	 TB 09642227210	<small>Blatt/ Page</small> 1 / 1	36283	09/12/11	SD	Stand.		33267	17/11/05	JMDR			31058	8-JUL-02	CV				Sub.		Mod.	Dat.	Name					
			Dat.	Name	 <small>All Dim. in mm Orig. Size DIN A 4</small>	D-Sub, male, straight, 15 Poles, solder pins, dimples and fixing holes	<small>M/MS tab/ Scale</small> 1.5:1																																																						
			Detail.	CV																																																									
			Insp.	JB	HARTING EURL F-95972 Paris	 TB 09642227210	<small>Blatt/ Page</small> 1 / 1																																																						
36283	09/12/11	SD	Stand.																																																										
33267	17/11/05	JMDR																																																											
31058	8-JUL-02	CV				Sub.																																																							
Mod.	Dat.	Name																																																											