

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[BUD Industries, Inc.](#)

[CU-742](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PART NAME	UTILIBOX (STYLE D)	PART No.	CU-742 & CU-744
------------------	--------------------	-----------------	-----------------

MATERIAL: HIGH-IMPACT POLYSTYRENE
COLOR: BLACK
FINISH: SMOOTH, MATTE

FOUR (4) #4 x 0.562' LG. SCREWS SUPPLIED FOR ASSEMBLY.

NOTE: ALL DIMENSIONS HAVE ±0.010 TOLERANCE UNLESS OTHERWISE SPECIFIED.

0.187 R. - TYP.
 2.500
 0.300
 3.000
 0.300 TYP.
 0.100
 0.300
 0.090 DIA. (4) HOLES
 0.220 DIA. (4) PLACES

0.218
 0.060 RECESS
 0.218
 1°
 0.100
 0.045
 0.125 R. TYP.
 0.260 DIA. BOSS (4) PLACES
 0.300
 0.300 TYP.
 0.300
 0.100
 0.095 R. TYP.
 0.055
 0.100 TYP.
 0.055
 0.225 DIA. C'BORE x 0.098 DEEP (4) PLACES

PART No.	A	B
CU-742	1.000	0.900
CU-744	1.600	1.500

PART NAME	PLASTIBOX (STYLE A)	PART No.	PT-11284 & PS-11285
------------------	---------------------	-----------------	---------------------

MATERIAL: HIGH-IMPACT ABS
COLOR: BLACK OR GRAY

FINISH: PREFIX PS- TEXTURED BODY WITH SMOOTH TOP INSERT. PREFIX PT- TEXTURED BODY WITH TEXTURED TOP.

SIX (6) #4 x 0.375' LG. SCREWS SUPPLIED FOR ASSEMBLING TOP.
 FOUR (4) NON-SKID PUSH-ON FEET SUPPLIED.

0.250 DIA. BOSS WITH 0.093 DIA. HOLE x 0.156 DEEP (8) PLACES
 MOUNTING BOSSES USE EITHER M2.5 METRIC OR #4 STD. SHEET METAL SCREWS x 0.188' LG. (NOT SUPPLIED)

*-USABLE AREA ON COVER ALSO AVAILABLE FOR CUSTOM MOLDING.

NOTE: ALL DIMENSIONS HAVE ±0.015 TOLERANCE UNLESS OTHERWISE SPECIFIED.

*9.140
 0.410
 0.900
 0.100
 0.250 DIA. BOSS WITH 0.093 DIA. HOLE x 0.156 DEEP (8) PLACES
 MOUNTING BOSSES USE EITHER M2.5 METRIC OR #4 STD. SHEET METAL SCREWS x 0.188' LG. (NOT SUPPLIED)

*5.980
 0.020 RECESS
 0.100 TYP.
 5° TYP.

9.500
 4.375
 3.875
 0.875
 0.100 R. TYP.
 0.420
 2.670 2.750
 6.340
 2.670 2.750
 0.420
 AREA FOR CUSTOM MOLDING.
 1.000
 1.000
 3.500
 3.500

0.250 DIA. BOSS WITH 0.093 DIA. HOLE x 0.310 DEEP (8) PLACES
 MOUNTING BOSSES USE EITHER M2.5 METRIC OR #4 STD. SHEET METAL SCREWS x 0.250' LG. (NOT SUPPLIED)