

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[111-00718](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

111-00718



Article Number: 111-00718

High Temp Cable Tie, 15" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 111-00718

Type T50L

Color Blue (BU)

- Features and Benefits**
- ETFE cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
  - Inside serrations allows for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** High Temp Cable Tie, 15" Long, 50lb Tensile Strength, ETFE, Blue, 100/pkg

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 222.3 N

Length L (Imperial) 15.0 "

Length L (Metric) 382 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.2 "

Bundle Diameter Min. (Metric) 5.0 mm

Bundle Diameter Max. (Imperial) 4.1 "

Bundle Diameter Max. (Metric) 105 mm

Thickness T (Imperial) 0.06 "

Cable Tie Head Length (Imperial) 0.34 "

Cable Tie Head Width (Imperial) 0.33 "

Thickness T (Metric) 1.7

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100 Pieces
<b>Carton Quantity</b>	2500
<b>Weight (Metric)</b>	2.7 kg

## Material and Specifications

---

<b>Material</b>	Ethylentetrafluoroethylene - (E/TFE)
<b>Material Shortcut</b>	E/TFE
<b>Flammability</b>	UL94 V0
<b>Operating Temperature</b>	-112°F to +338°F (-80°C to +170°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	Det Norske Veritas
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes