

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[126-00086](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

126-00086

Article Number: 126-00086

Domed Low Profile Mount Ties, 6.2" Long, Mounting Hole Diameter .25" - .26", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 126-00086

Type T50SOSKSFT6.5S2-E

Color Black (BK)

- Features and Benefits**
- Dome provides a tight, rattle-free installation.
  - Outside serrated strap has ribs designed for convoluted tubing.
  - Dome acts as a seal to keep out dust and liquid.

**Product Description** HellermannTyton's low profile push mount design provides an overall shortened length which assists in limiting protrusion on the opposing side of application surfaces. The rounded tip of the mount allows for a smoother surface in case of contact with surrounding components or human touch during service.

**Short Description** Domed Low Profile Mount Ties, 6.2" Long, Mounting Hole Diameter .25" - .26", PA66HS, Black, 500/pkg

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.2 "

Length L (Metric) 157.5 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.58 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.3 mm

Panel Thickness Min. (Imperial) 0.07 "

<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.26 "		
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.248 "	<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.264 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	6.7 mm	<b>Mounting Hole Diameter D Min. (Metric)</b>	6.3 mm
<b>Thickness T (Metric)</b>	1.3 mm	<b>Thickness T (Imperial)</b>	0.05 "

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500 Pieces
<b>Carton Quantity</b>	5000 Pieces
<b>Weight (Metric)</b>	1.3 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes