

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[148-90026](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

148-90026



Article Number: 148-90026

HelaCon Plus Push-In Style Wire Connector, Double Spring, 4-Port, Polycarbonate, Clear, 300/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 148-90026

Type HECP-4

Color Clear (CL)

**Features and Benefits** Double Spring Technology for safe, secure and reliable connections  
 Low Insertion Forces + High Retention Values  
 Accommodates both solid and stranded wire cores  
 Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards  
 Low insertion forces reduces buckling of stranded wire  
 Able to combine solid and stranded within same housing  
 Separate test port for fast, easy confirmation of connection  
 Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.  
 Max Current Rating to 24 A  
 Max Voltage Rating to 600 V (c UL us)

**Short Description** HelaCon Plus Push-In Style Wire Connector, Double Spring, 4-Port, Polycarbonate, Clear, 300/pkg

## Product Dimensions

Length L (Imperial) 0.41 "

Length L (Metric) 10.45 mm

Max Current 24 A

Max Voltage 600 V

Number of Conductors 4

Stripping Length 11 mm

Suitable for multi wire core (Yes/No) Yes

Width W (Imperial) 0.79 "

Width W (Metric) 20.05 mm

Height H (Imperial) 0.41 "

Height H (Metric) 10.45 mm

Depth D (metric) 19.0 mm

Depth D (imperial) 0.75 "

## Logistics and Packaging

Quantity Per bag

Package Quantity 300

Carton Quantity 3000

## Material and Specifications

---

<b>Material</b>	Polycarbonate (PC)
<b>Material Shortcut</b>	PC
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-22°F to +230°F (-30°C to +110°C) -22°F to +221°F (-30°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	SEMKO FIMKO CEN GL KEMA-KEUR VDE ENEC cULus NEMKO DEMKO
<b>UL Listed (US and Canada)</b>	Yes