

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[148-90027](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

148-90027



Article Number: 148-90027

Helacon Plus Push-In Style Wire Connector, Double Spring, 5-Port, Polycarbonate, Blue, 300/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 148-90027

Type HECP-5

Color Clear (CL)
Blue (BU)

Features and Benefits Double Spring Technology for safe, secure and reliable connections
Low Insertion Forces + High Retention Values
Accommodates both solid and stranded wire cores
Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards
Low insertion forces reduces buckling of stranded wire
Able to combine solid and stranded within same housing
Separate test port for fast, easy confirmation of connection
Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.
Max Current Rating to 24 A
Max Voltage Rating to 600 V (c UL us)

Short Description Helacon Plus Push-In Style Wire Connector, Double Spring, 5-Port, Polycarbonate, Blue, 300/pkg

Product Dimensions

Length L (Imperial) 0.41 "

Length L (Metric) 10.45 mm

Max Current 24 A

Max Voltage 600 V

Number of Conductors 5

Stripping Length 11 mm

Suitable for multi wire core (Yes/No) Yes

Width W (Imperial) 0.95 "

Width W (Metric) 24.20 mm

Height H (Imperial) 0.41 "

Height H (Metric) 10.45 mm

Depth D (metric) 19.0 mm

Depth D (imperial) 0.75 "

Logistics and Packaging

Quantity Per bag

Package Quantity 300

Package Quantity (Metric) 50

Carton Quantity 3000

Weight (imperial) 3.94 lbs

Material and Specifications

Material Polycarbonate (PC)

Material Shortcut PC

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -22°F to +230°F (-30°C to +110°C)
-22°F to +221°F (-30°C to +105°C)

ROHS Compliant Yes

Certification/Specification CEN
SEMKO
VDE
ENEC
FIMKO
DEMKO
GL
KEMA-KEUR
cULus
NEMKO

UL Listed (US and Canada) Yes