

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[151-00366](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

151-00366



Article Number: 151-00366

Automatic Harness Clips - Non-Connectable Push Mount Max Bun Dia .51" Black 100 Pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00366

Type AHC1AH

Color Black (BK)

Features and Benefits These clips offer a simple and secure method of attaching cables to panels. They can be attached to the panel prior to installing the cables. Simply pushing the cable into place closes the clip and activates the automatic locking feature.

Short Description Automatic Harness Clips - Non-Connectable Push Mount Max Bun Dia .51" Black 100 Pkg

Product Dimensions

Length L (Imperial) 0.98 "

Length L (Metric) 24.0 mm

Length L2 (Imperial) 0.28 "

Length L2 (Metric) 7.0 mm

Fixation Method Snapper mounting

Width W (Imperial) 0.39 "

Width W (Metric) 10.0 mm

Bundle Diameter Min. (Imperial) 0.12 "

Bundle Diameter Min. (Metric) 3.0 mm

Bundle Diameter Max. (Imperial) 0.51 "

Bundle Diameter Max. (Metric) 13.0 mm

Disc Diameter (Imperial) 0.79 "

Disc Diameter (Metric) 20.0 mm

Panel Thickness Max. (Imperial) 0.08 "

Panel Thickness Max. (Metric) 2.00 mm

Panel Thickness Min. (Imperial) 0.02 "

Panel Thickness Min. (Metric) 0.50 mm

Mounting Hole Diameter D (Metric) 6.2 - 6.7 mm

Mounting Hole Diameter D Min. 0.244 "

(Imperial)

Mounting Hole Diameter D Max.0.26 "

(Imperial)

Mounting Hole Diameter D Max.6.7 mm

(Metric)6.2 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging



Quantity Per	carton
Package Quantity (Metric)	1500 Pieces
Carton Quantity	1500
Weight (Metric)	0.5 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes