

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[151-00775](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

151-00775



Article Number: 151-00775



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00775

Type CCSFT6.5

Color Black (BK)

Features and Benefits Connector Clips are initially installed onto the appropriate mating connector found on a wire or cable harness assembly. The connector is then secured to the attachment surface using the connector clip mount. The attachment surface can be a hole, stud, or even another harness assembly depending on the connector clip mount being used.

Product Dimensions

Length L (Imperial) 0.91 "

Length L (Metric) 23.0 mm

Fixation Method Arrowhead (Small Mount)

Height H (Imperial) 0.48 "

Height H (Metric) 12.1 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.3 mm

Panel Thickness Min. (Imperial) 0.07 "

Panel Thickness Min. (Metric) 1.7 mm

Mounting Hole Diameter D (Imperial) 0.25-0.26 "

Mounting Hole Diameter D (Metric) 6.3 - 6.7 mm

Mounting Hole Diameter D Min. 0.24 "

(Imperial) **Mounting Hole Diameter D Max.0.26 "**
(Imperial)

Mounting Hole Diameter D Max.6.7 mm
(Metric) 6.3 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 5000

Carton Quantity 5000 Pieces

Weight (Metric) 0.575 kg

Material and Specifications



Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes