

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[155-05400](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

155-05400



Article Number: 155-05400

Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 155-05400

Type T50SOSSB5HEC

Color Black (BK)

Features and Benefits

- Oval mount design pushes on easy by hand without the need for tools.
- Design provides low insertion and high extraction force.

Product Description The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables

Short Description Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 170 N

Length L (Imperial) 6.0 "

Length L (Metric) 160 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.6 mm

Height H2 (Imperial) 0.63 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Stud Length min (metric) 11.0 mm

Stud Length Max. (Imperial) 0.63 "

Stud Length Max. (Metric) 16.0 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.35 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm



Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500 Pieces
Carton Quantity	3000 Pieces
Weight (Metric)	2.75 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes