

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[156-00069](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

156-00069



Article Number: 156-00069

Heavy Duty Fir Tree Mount and Cable Tie, 120lb, 12.0" Long, PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00069

Type WSIFT9A

Color Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
 - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
 - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

Product Description HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

Short Description Heavy Duty Fir Tree Mount and Cable Tie, 120lb, 12.0" Long, PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 15.0 "

Length L (Metric) 387.0 mm

Fixation Method Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.6 mm

Width W2 (Imperial) 0.51 "

Width W2 (Metric) 13.0 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.1 mm

Height H2 (Imperial) 0.36 "

Height H2 (Metric) 9.0 mm

Bundle Diameter Max. (Imperial) 4.0 "

Bundle Diameter Max. (Metric) 102.0 mm

Disc Diameter (Imperial) 0.85 "

Disc Diameter (Metric) 21.6 mm

Panel Thickness Max. (Imperial) 0.25 "

Panel Thickness Max. (Metric)	6.5 mm
Panel Thickness Min. (Imperial)	0.03 "
Panel Thickness Min. (Metric)	1.0 mm
Mounting Hole Diameter D (Metric)	8.75 - 9.25 mm
Mounting Hole Diameter D Min. (Imperial)	0.34 "
Mounting Hole Diameter D Max. (Imperial)	0.36 "
Diameter Min. (Imperial)	0.85 "
Diameter Min. (Metric)	21.6 mm
Mounting Hole Diameter D Max. (Metric)	9.25 mm
Mounting Hole Diameter D Min. (Metric)	8.75 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100
Carton Quantity	1000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes