

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[157-00106](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

157-00106



Article Number: 157-00106

Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 157-00106

Type T50SOSSB5-High-E-O-US

Color Black (BK)

Features and Benefits

- Head allows for a .2" lateral adjustment on stud during installation.
- Quick and easy installation ideal for manufacturing environment.

Product Description Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.

Short Description Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.6 "

Length L (Metric) 167.0 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.2 "

Width W (Metric) 5.0 mm

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

## Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

## Material and Specifications



**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes