



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 157-00404 - WDE TIE W/3/8" STD 120LB 12.7"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[157-00404](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

157-00404



Article Number: 157-00404

Wide Strap Tie with 0.38" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00404

Type WSI380

Color Black (BK)

Features and Benefits

- Applies to threaded studs for quick and easy installation.
- Design of strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses.
- Strap is flexible and utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

Product Description The Wide Strap Heavy Duty Cable Tie features a stud mount for direct application onto a 3/8" threaded stud. The design of the strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses. The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. A thinner strap provides increased flexibility for improved ergonomics.

Short Description Wide Strap Tie with 0.38" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 12.7 "

Length L (Metric) 322.6 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.38 "

Bundle Diameter Min. (Metric) 9.5 mm

Bundle Diameter Max. (Imperial) 3.3 "

Bundle Diameter Max. (Metric) 82.5 mm

Stud Size (Imperial) 0.375 "

Stud Size (Metric) 9.52 mm

Logistics and Packaging

Quantity Per bag



Carton Quantity 1200

Weight (Metric) 7.22 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes